

AXIS Camera Station S2208 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2208 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2208 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 8 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2208 provides a reliable surveillance solution.

- > [All-in-one solution with integrated PoE switch](#)
- > [High-definition surveillance with up to 4K resolution](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)



AXIS Camera Station S2208 Appliance

Licenses	8 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view Supports only one monitor
System scalability	Qualified for up to 8 video channels and 16 doors	Recording
Hardware		Qualified for recording up to 8 video channels with a total recording rate up to 128 Mbit per second
Processor	Intel® Core™ i3	General
Memory	8 GB	Operating system
Storage	Surveillance Class HDD Total HDD slot: 2 Free HDD slot: 1 Out-of-the-box storage: 4 TB (1x4 TB)	Microsoft® Windows® 10 IoT Enterprise Operating system recovery: yes Operating system drive: 120 GB SSD
Switch	8 ports integrated, 135 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	Security
Graphics card	Intel® HD Graphics	Security support for encrypted operating system drive and recording drive FIPS 140-2 level 2 certified Trusted Platform Module (TPM 2.0)
Power	Max 270 W, 135 W PoE dedicated 100 - 240 V AC, 3.5 A, 50/60 Hz 54 V DC, 5 A External power adapter	Operating conditions
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 8x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port	Storage conditions
Video		Approvals
Video streaming	Live view: 1 x 4K stream full screen 4 split x 1080p Up to 8 cameras split view	EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252
		Dimensions
		Weight
		Included accessories
		Optional accessories
		Warranty

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com