

AXIS TW1200 Body Worn Mini Bullet Sensor

External sensor for Axis body worn cameras

AXIS TW1200 Body Worn Mini Bullet Sensor is designed to offer a exible recording position. It supports the Picatinny mounting system, making it compatible with many kinds of available gear, and especially suitable for helmets. AXIS TW1200 offers the same optical performance as AXIS W100 with sharp images even in challenging conditions.

- > Small and discreet
- > Lightweight
- > Same optical performance as the AXIS W100
- > Compatible with Picatinny system
- > For use with AXIS W100



AXIS TW1200 Body Worn Mini Bullet Sensor

Camera	
Image sensor	1/2.9" progressive scan RGB CMOS Sensitivity: 0.1 lux
Lens	Focal length, 2.1 mm Horizontal eld of view: 141° Vertical eld of view: 82° Fixed iris, F2.1
Shutter speed	1/32000 s to 1/25 s with 50 Hz 1/32000 s to 1/30 s with 60 Hz
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) High Pro le (with AXIS W100)
Resolution	1920x1080, 1280x720
Frame rate	25 fps at 50 Hz 30 fps at 60 Hz
Wide dynamic range	WDR (with AXIS W100)
Video streaming	Axis Zipstream for body worn (with AXIS W100)
General	
Casing	IP67-rated Aluminum casing, polycarbonate (PC) hard coated dome Color: black NCS S 9000-N
Sustainability	PVC free
Connectors	USB
Mounting	Picatinny system (MIL-STD-1913 rail)

Operating conditions	-20 °C to 55 °C (-4 °F to 131 °F) Humidity 10–100% RH (non-condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5-95% RH (non-condensing)
Approvals	EMC EN 55032 Class B, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), RCM AS/NZS CISPR 32 Class B Safety IEC/EN 62368-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC/EN 60529 IP67 MIL-STD-810H (Method 501.7, 503.7, 505.7, 509.7, 512.6, 516.8)
Dimensions	Length: 68 mm (2.7 in) Diameter: ø 23 mm (0.9 in) Cable length: 0.8 m (2.6 ft)
Weight	60 g (0.13 lb)
Included accessories	AXIS TW1900 Adhesive Picatinny Rail, AXIS TW1901 Cable Holder, AXIS TW1903 Picatinny Mount
Optional accessories	AXIS TW1900 Adhesive Picatinny Rail, AXIS TW1901 Cable Holder, AXIS TW1902 Lens Protector, AXIS TW1903 Picatinny Mount For more accessories, see axis.com
Warranty	3-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility

