

AXIS TQ6501-E Parapet Mount

Parapet mount with conduit side entry

AXIS TQ6501-E Parapet Mount is a robust, outdoor-ready mount made of aluminum. The round base of the mount makes it easy to install as well as suitable for installations on poles. It's compatible with Axis pendant kits with 1.5" NPS or NPT inner thread which enables mounting of several Axis cameras, and Axis ACI ¾" conduit adapters. Cables can be routed through the bottom, or from the side by using a conduit connection. AXIS TQ6501-E has four holes for standard pole mounted pan and tilt camera xings, equi-spaced on 101.6 PCD.

- > Outdoor-ready
- > Lightweight, made of aluminium
- > Robust, IK10-rated
- > Easy to install
- > Compatible with standard pan tilt pole mounted camera fixings





www.axis.com T10153005/EN/M5.2/2202

AXIS TQ6501-E Parapet Mount

General	
Supported products	AXIS P56 Series ^a AXIS Q60 Series ^a AXIS Q61 Series ^a AXIS M5525–E ^a
Optional accessories	AXIS ACI Conduit Adapter 3/4" U-shape 30 mm AXIS ACI Conduit Adapter 3/4" NPS AXIS Bird Control Spike AXIS 794A01D Pendant Kit AXIS 794B02D Pendant Kit AXIS 794F01D Pendant Kit AXIS 794F01D Pendant Kit with Sunshield AXIS 794K01D Pendant Kit AXIS 794K01D Pendant Kit AXIS 794M01D Pendant Kit AXIS 794M01D Pendant Kit AXIS 794M01D Pendant Kit AXIS 794N01D Pendant Kit AXIS 79402D Pendant Kit AXIS 794701D Pendant Kit AXIS 794V01C Dual Camera Mount AXIS 794V01D Pendant Kit AXIS 794V01D Pendant Kit AXIS 794V01D Pendant Kit
Environment	Outdoor Indoor

Maximum load	40 kg (88 lb)
Casing	IK10-rated Aluminium Color: White NCS S 1002-B This product can be repainted
Cable routing	Bottom: Cable hole Side: Cable conduit hole M20 (3/4")
Sustainability	PVC free Halogen free
Dimensions	Height: 754 mm (29.69 in) Width: 160 mm (6.3 in) Depth/Length: 418 mm (16.46 in)
Weight	2.5 kg (5.51 lb)
Included accessories	Installation guide, AXIS T91A6 Pipe Seal
Warranty	Axis 3-year warranty, see www.axis.com/warranty

a. Requires T94A01D Pendant Kit

Environmental responsibility: axis.com/environmental-responsibility

