essential

LIGHT WINGS

IMPRESSIVE LIGHTING, SUPERIOR COOLING

140mm PWM high-speed • 140mm PWM
120mm PWM high-speed • 120mm PWM

IDEAL APPLICATIONS

Gaming and multimedia systems
Showcases with glass and mesh openings
Water-cooled and air-cooled systems that demand high performance

HIGHLIGHTS

ARGB lighting with multiple colors and options
Optimized fan blades for high airflow and air pressure
Quiet and noise-reduced operation

Highlights »

- ARGB lighting on front and rear
- Multiple colors and modes for an individual look thanks to having up to 20 LEDs
- Illumination can be synced with the ARGB adjustments of the motherboard
- Choice of silence optimized fan blades for high airflow or performance optimized fan blades for maximum air pressure
- ARGB Hub allows you to synchronize up to six ARGB components (Triple pack only)
- Long life rifle-bearing gives an operating lifetime of 60,000 hours
- PWM controlled fan speed through the motherboard
- Three-year manufacturer’s warranty
- Product conception, design and quality control in Germany

We do not take responsibility for typographical errors. Similar Image.

LIGHT WINGS

IMPRESSIVE LIGHTING, SUPERIOR COOLING

Technical Data Single Pack »				
Model	140mm PWM high-speed	140mm PWM	120mm PWM high-speed	120mm PWM
Article no.	BL075	BL074	BL073	BL072
EAN Code	4260052188798	4260052188781	4260052188774	4260052188767
Dimensions, (W x H x D in mm)	140 x 140 x 25	140 x 140 x 25	120 x 120 x 25	120 x 120 x 25
Fan speed (rpm) @ 100% PWM	2,200	1,500	2,500	1,700
Noise level (dB(A)) @ 100% PWM	31	23.3	31	20.6
Airflow @ 100% PWM (cfm/m³)	71.7 / 121.82	56.0 / 95.14	52.3 / 88.86	41.51 / 70.53
Air pressure (mm / H2O)	2.3	1.49	2.6	1.66
Voltage range DC (V)	7 - 13.2	7 - 13.2	7 - 13.2	7 - 13.2
Input power (W)	4.68	3.84	5.4	4.56
Input current (A)	0.39	0.32	0.45	0.38
Lighting	5V ARGB connector	5V ARGB connector	5V ARGB connector	5V ARGB connector
Connector	4-pin PWM	4-pin PWM	4-pin PWM	4-pin PWM
Lifetime @ 25°C (h)	up to 60,000	up to 60,000	up to 60,000	up to 60,000
Accessories	manual, fan screws			

Technical Data Triple Pack »				
Model	140mm PWM high-speed	140mm PWM	120mm PWM high-speed	120mm PWM
Article no.	BL079	BL078	BL077	BL076
EAN Code	4260052188835	4260052188828	4260052188811	4260052188804
Dimensions, (W x H x D in mm)	140 x 140 x 25	140 x 140 x 25	120 x 120 x 25	120 x 120 x 25
Fan speed (rpm) @ 100% PWM	2,200	1,500	2,500	1,700
Noise level (dB(A)) @ 100% PWM	31	23.3	31	20.6
Airflow @ 100% PWM (cfm/m³)	71.7 / 121.82	56.0 / 95.14	52.3 / 88.86	41.51 / 70.53
Air pressure (mm / H2O)	2.3	1.49	2.6	1.66
Voltage range DC (V)	7 - 13.2	7 - 13.2	7 - 13.2	7 - 13.2
Input power (W)	4.68	3.84	5.4	4.56
Input current (A)	0.39	0.32	0.45	0.38
Lighting	5V ARGB connector	5V ARGB connector	5V ARGB connector	5V ARGB connector
Connector	4-pin PWM	4-pin PWM	4-pin PWM	4-pin PWM
Lifetime @ 25°C (h)	up to 60,000	up to 60,000	up to 60,000	up to 60,000
Accessories	ARGB Hub, ARGB cable, double coated tissue tape, manual, fan screws, fastening screws for ARGB Hub			

Certifications »

RoHS COMPLIANT

CE

c UL us E360596

Contact »

be quiet! Headquarters

Listan GmbH
Wilhelm-Bergner-Straße 11c
21509 Glinde
Germany

Service hotline: +49 40 7367 686 44

e-mail: service@bequiet.com
Visit the contact section on bequiet.com
for the right regional service information.

V1/21

We do not take responsibility for typographical errors. Similar image.