



APC Smart-UPS, Line Interactive, 750VA, Rackmount 2U, 230V, 4x IEC C13 outlets, Network Card, AVR, LCD

Brand : APC

Product code: SMT750RMI2UNC

Product name : Smart-UPS, Line Interactive, 750VA, Rackmount 2U, 230V, 4x IEC C13 outlets, Network Card, AVR, LCD



Smart-UPS, Line Interactive, 750VA, Rackmount 2U, 230V, 4x IEC C13 outlets, Network Card, AVR, LCD
APC Smart-UPS, Line Interactive, 750VA, Rackmount 2U, 230V, 4x IEC C13 outlets, Network Card, AVR, LCD. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 500 W. AC outlet types: C13 coupler, C14 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 168 Ah, Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 406 mm, Height: 89 mm



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Output power capacity *	0.75 kVA	Rack capacity	2U
Output power *	500 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	151 V	LED indicators	✓
Input operation voltage (max) *	302 V	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Input frequency *	50/60 Hz		
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Output frequency regulation	+/- 3 Hz	Operating relative humidity (H-H)	0 - 95%
Output voltage regulation	5%	Storage relative humidity (H-H)	0 - 95%
Surge energy rating	459 J	Operating altitude	0 - 3000 m
Response time	2 ms	Non-operating altitude	0 - 15000 m
Emergency Power Off (EPO)	0	Technical details	
Noise level	46 dB	Sustainability certificates	Green Premium
Surge protection	✓	Compliance certificates	RoHS
Audible alarm(s)	✓	Weight & dimensions	
Web-based management	✓	Width	432 mm
Audible alarm modes	Battery replacement	Depth	406 mm
Auto-restart	✓	Height	89 mm
Ports & interfaces		Weight	17.2 kg
AC outlet types	C13 coupler, C14 coupler	Package width	546 mm
Power plug	C14 coupler	Package depth	584 mm
AC outlets quantity	4 AC outlet(s)	Package height	241 mm
USB 2.0 ports quantity	1	Package weight	21.2 kg
Ethernet LAN (RJ-45) ports	1	Packaging data	
Battery		Rack mount kit	✓
Battery technology	Sealed Lead Acid (VRLA)	Cables included	Input power cable, USB cable
Battery capacity	168 Ah	Quick installation guide	✓
Battery recharge time	3 h	Resource CD	✓
Hot-swap battery	✓	Logistics data	
Automatic battery test	✓	Products per pallet	16 pc(s)
Cold start	✓	Harmonized System (HS) code	85078000

Other features

Output voltage	230 V
----------------	-------



0731304327721



731304327721

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.