EPSON

Epson WorkForce DS-1630 Flatbed scanner 600 x 600 DPI A4 Black, White

Brand : Epson   **Product family:** WorkForce   **Product code:** B11B239401BY

Product name : DS-1630

A4, Flatbed, 600 x 600DPI, ReadyScan LED, Duplex, USB 3.0, 55dB
Epson WorkForce DS-1630. Maximum scan size: 210 x 3048 mm, Optical scanning resolution: 600 x 600 DPI, Enhanced scan resolution: 1200 x 1200 DPI. Scanner type: Flatbed scanner, Product colour: Black, White, Display: LCD. Daily duty cycle (max): 1500 pages, Light source: ReadyScan LED, Scan file formats: PDF, TIFF. Auto document feeder (ADF) input capacity: 50 sheets. Maximum ISO A-series paper size: A4, ISO A-series sizes (A0...A9): A4, A5, A6, ISO B-series sizes (B0...B9): B5

Scanning

Maximum scan size *	210 x 3048 mm
Optical scanning resolution *	600 x 600 DPI
Enhanced scan resolution	1200 x 1200 DPI
Colour scanning	✓
Duplex scanning *	✓
ADF scan speed (b/w, A4)	25 ppm
ADF scan speed (colour, A4)	25 ppm

Design

Scanner type *	Flatbed scanner
Product colour *	Black, White
Display	LCD
Built-in display *	✗

Performance

Light source	ReadyScan LED
Scan file formats	PDF, TIFF
Daily duty cycle (max) *	1500 pages
Scan drivers	ISIS, TWAIN
Scanning noise level	55 dB

Input capacity

Auto document feeder (ADF) input capacity	50 sheets

Paper handling

Maximum ISO A-series paper size *	A4
ISO A-series sizes (A0...A9)	A4, A5, A6
ISO B-series sizes (B0...B9)	B5
Letter	✓
Legal	✓
Auto Document Feeder (ADF) media weight	50 - 120 g/m²
Maximum scan area (ADF)	89 x 127 mm

Paper handling

Minimum scan area (ADF)	210 x 3048 mm

Ports & interfaces

USB port *	✓
USB version	3.2 Gen 1 (3.1 Gen 1)
Standard interfaces	USB 3.2 Gen 1 (3.1 Gen 1)

Network

Supported network protocols	TCP/IP, DHCP, DNS, SNMP, SLP

Power

Power supply type *	AC

Weight & dimensions

Width	451 mm
Depth	315 mm
Height	120 mm
Weight	3.7 kg

Packaging content

Cables included	AC, USB
Drivers included	✓

Sustainability

Sustainability certificates	ENERGY STAR

System requirements

Windows operating systems supported	✓

Operational conditions

Operating temperature (T-T)	10 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	20 - 80%

Logistics data

Harmonized System (HS) code	84716070

8715946619064