

## Epson DS-410 Sheet-fed scanner 600 x 600 DPI A4 Black, White

Brand : Epson

Product code: B11B249401BY

Product name : DS-410

215.9 x 3048mm, 600x600DPI, CIS, 50 - 209 g/m², 297x152x154mm, 2.5kg

Epson DS-410. Maximum scan size: 215.9 x 3048 mm, Optical scanning resolution: 600 x 600 DPI, Input colour depth: 10 bit. Scanner type: Sheet-fed scanner, Product colour: Black, White. Sensor type: CIS, Daily duty cycle (max): 3000 pages, Scan file formats: BMP, JPG, PDF, PNG, TIFF. Standard input capacity: 50 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Post Card(JPN), ISO A-series sizes (A0...A9): A4, A5, A6







Scanning		Ports & interfaces		
		USB version	2.0	
		Standard interfaces	USB 2.0	
		Power		
	10 bit 8 bit 26 ppm	Power supply type * Power consumption (off) AC input frequency Input voltage Power supply	AC 0.2 W 50 - 60 Hz 100 - 120 V 15 W	
Design		Weight & dimensions		
Scanner type * Product colour * Built-in display * <b>Performance</b>	Sheet-fed scanner Black, White X	Width Depth Height	297 mm 152 mm 154 mm	
		Weight	2.5 kg	
Sensor type * Scan file formats	CIS BMP, JPG, PDF, PNG, TIFF	Packaging content		
Daily duty cycle (max) *	3000 pages	Cables included	AC, USB	
Scan drivers	ISIS, TWAIN, WIA	Bundled software	Document Capture Pro 2.0, Epson Scan 2	
Input capacity		Sustainability		
Standard input capacity	50 sheets	Sustainability certificates	ENERGY STAR	
Paper handling		System requirements		
Scanning media types supported Maximum ISO A-series paper size *	Business Card, Post Card(JPN) A4	Windows operating systems supported	4	
ISO A-series sizes (A0A9)	A4, A5, A6	Mac operating systems supported	1	
Letter 🗸		Server operating systems supported	Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2	
Legal Auto Document Feeder (ADF) media weight	✓ 50 - 209 g/m²	Operational conditions		
		Operating temperature (T-T)	5 - 35 °C	
		Operating relative humidity (H-H)	15 - 80%	

Ports & interfaces		Operational of	conditions
USB port *	<	Storage relativ	ve humidity (H-H) 15 - 85%
		Logistics dat	ta
		Harmonized S	System (HS) code 84716070



## 8715946638713

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.