



# D-Link DGS-1210-10P network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black



**Brand :** D-Link

**Product code:** DGS-1210-10P

**Product name :** DGS-1210-10P

- Layer 2 management and security with Layer 3 capabilities
- Compact Command-Line Interface (CLI) and web-based User-Interface
- Static Routing and MSTP
- PoE options up to 370W power budget
- Dual image & config

DGS-1210-10P - 8-port PoE/PoE+ Gigabit WebSmart Switch with 2 Combo 1000 Base-T/SFP Ports  
 D-Link DGS-1210-10P. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Power connector: DC-in jack. Power over Ethernet (PoE). Rack mounting, Form factor: 1U

Management features		Power over Ethernet (PoE)	
Switch type *	Managed	Power over Ethernet (PoE) ports quantity	8
Switch layer	L2	Power over Ethernet plus (PoE+) ports quantity	2
Quality of Service (QoS) support	✓	Total Power over Ethernet (PoE) budget	78 W
Web-based management	✓		
Ports & interfaces		Operational conditions	
Basic switching RJ-45 Ethernet ports quantity *	8	Operating temperature (T-T)	-5 - 50 °C
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Storage temperature (T-T)	-20 - 70 °C
Gigabit Ethernet (copper) ports quantity	8	Operating relative humidity (H-H)	0 - 95%
SFP module slots quantity	2	Storage relative humidity (H-H)	0 - 95%
Power connector	DC-in jack	Heat dissipation	373.96 BTU/h
Network		Weight & dimensions	
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Width	280 mm
10G support *	✗	Depth	126 mm
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T	Height	44 mm
Cable types supported	Cat5, Cat5e	Weight	950 g
Port mirroring	✓	Packaging data	
Full duplex	✓	Package width	288 mm
Flow control support	✓	Package depth	331 mm
Link aggregation	✓	Package height	72 mm
Auto MDI/MDI-X	✓	Package weight	2.21 kg
Data transmission		Technical details	
Switching capacity *	20 Gbit/s	Shipping (inner) case height	31.7 cm
Forwarding rate	14.88 Mpps	Shipping (inner) case width	34.6 cm
MAC address table *	8000 entries	Shipping (inner) case length	38.2 cm
Store-and-forward	✓	Shipping (inner) case net weight	11.1 kg
Packet buffer memory	0.512 MB	Products per shipping (inner) case	5 pc(s)
Security		Pallet gross weight (air)	449.5 kg
Access Control List (ACL)	✓	Master (outer) cases per pallet (air)	36 pc(s)
MAC address filtering	✓	Products per pallet (air)	180 pc(s)
Multicast features		Pallet gross length	110 cm
Multicast support	✓	Pallet gross width	120 cm
Design		Pallet height (air)	140.3 cm
Rack mounting *	✓	Pallet gross weight (sea)	662 kg
		Master (outer) cases per pallet (sea)	54 pc(s)
		Products per pallet (sea)	270 pc(s)
		Pallet height (sea)	2.04 m

Design		Technical details	
Stackable *	✓	Shipping (inner) case gross weight	11.8 kg
Form factor	1U	<b>Certificates</b>	
Product colour	Black	Certification	EMI: CE Class A, VCCI Class A, FCC Class A, BSMI, CCC
LED indicators	✓	<b>Logistics data</b>	
Performance		Harmonized System (HS) code	85176990
Noise level	0 dB		
Mean time between failures (MTBF)	729258 h		
Power			
Power consumption (max)	80.6 W		
Power over Ethernet (PoE)			
Power over Ethernet (PoE) *	✓		



0790069329432



790069329432




0790069329395



790069329395



0790069329401



790069329401



0790069329388



790069329388

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.