Manhattan Mini DisplayPort 1.2 to HDMI Adapter Cable, 1080p@60Hz, 12cm, Male to Female, Black, Equivalent to MDP2HDMI, Three Year Warranty, Polybag

Brand : Manhattan

Product code: 151528

Product name : Mini DisplayPort 1.2 to HDMI Adapter Cable, 1080p@60Hz, 12cm, Male to Female, Black, Equivalent to MDP2HDMI, Three Year Warranty, Polybag

Mini DisplayPort to HDMI Adapter Cable, 1080p, Passive, Male to Female, 12cm, Black, Polybag

Manhattan Mini DisplayPort 1.2 to HDMI Adapter Cable, 1080p@60Hz, 12cm, Male to Female, Black, Equivalent to MDP2HDMI, Three Year Warranty, Polybag:

Easily connect a Mini DisplayPort source to an HDMI cable.

The Manhattan Passive Mini DisplayPort to HDMI Adapter establishes a fast, simple and convenient connection between a Mini DisplayPort media source and an HDMI display. This passive adapter requires a DP++ (dual-mode) video/graphics cards on the media source to regenerate the signal and ensure the best connection to an HD display. Ideal for presentations, retail displays and other uses, this single solution is easy and quick to install and requires no complicated configuration or setup. With the Manhattan Passive Mini DisplayPort to HDMI Adapter, users will be able to fully realise the investment, value and service life of HDMI displays. It offers a passive, compact and integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly.

Features

Connector 1 form factor
Connector 2 form factor
Connector contacts plating
Cable length *
Connector 1 *
Connector 2 *
Connector 1 gender *
Connector 2 gender *
DisplayPort version
Dual Link DVI
Maximum resolution
Supported video modes
Data transfer rate
Product colour
AWG wire size
Colour depth

Straight Straight Nickel 0.12 m Mini DisplayPort HDMI Type A (Standard) Male Female 1.2 1 1920 x 1200 pixels 1080p 10.8 Gbit/s Black 30 10 bit

Features	
Converter type Cable shielding Connector gender Certification	Passive video converter Aluminium mylar foil Male/Female UL 20276
Operational conditions	
Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Weight & dimensions	
Weight Width Depth Height	53 g 20 mm 170 mm 11 mm
Packaging data	
Quantity per pack Package type	1 pc(s) Polybag
Logistics data	
Harmonized System (HS) code	84733080







766623151528

0766623151528

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.