

CyberPower PDU81405 power distribution unit (PDU) 24 AC outlet(s) 0U Black

Brand : CyberPower

Firmware upgradeable

Firmware upgradeable via

Product code: PDU81405

Product name : PDU81405



21xC13, 3xC19, 220-240V, 50/60Hz, 16A, 1665x56x48mm, 7kg, Black

CyberPower PDU81405. PDU types: Metered, Monitored, Switched, Rack capacity: 0U, Type: Singlephase. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC 60309. Cable length: 3.05 m, Certification: CE, EN 55032 Class A. Supported network protocols: IPv4/v6, SNMPv1/v3, HTTP/HTTPs, TCP/IP, UDP, DHCP, NTP, DNS, SMTP, SSH, SSL, TLS, Telnet, FTP, and..., Firmware upgradeable via: USB. Nominal input voltage: 200-240 V, Maximum current: 16 A, AC input frequency: 50 / 60 Hz

and Syslog

1

USB

| Design | | Power | |
|---|--|--|--|
| , | Metered, Monitored, Switched Single-phase 0U | Nominal input voltage * AC input frequency Maximum current * | 200-240 V 50 / 60 Hz 16 A |
| Mounting | Vertical | Weight & dimensions | |
| Housing material Product colour Display | Metal Black LCD | Width Depth Height | 1665 mm 56 mm 48 mm |
| Ports & interfaces | | Weight | 7 kg |
| AC outlets quantity*24 AC outlet(s)Power plugIEC 60309AC outlet types*C13 coupler, C19 couplerSerial ports quantity1Ethernet LAN (RJ-45) ports3 | | Packaging data | |
| | Package weight Package width Package depth Package height | 8.9 kg 1895 mm 185 mm 115 mm | |
| Features | | Operational conditions | |
| Daisy chain LED indicators Cable length Certification | ✓ ✓ 3.05 m CE, EN 55032 Class A | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) | 0 - 55 °C -15 - 60 °C 0 - 95% 0 - 95% |
| Management features | | Operating altitude | 0 - 3500 m |
| Supported network protocols | IPv4/v6, SNMPv1/v3, HTTP/HTTPs, TCP/IP, UDP, DHCP, NTP, DNS, SMTP, SSH, SSL, TLS, Telnet, FTP, | Non-operating altitude | 0 - 15000 m |

Publication date: 14-NOV-2024. Prints or copies of Information are only valid on the printed Publication date

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.