MSI MPG A850GF UK PSU '850W, 80 Plus Gold certified, Fully Modular, 100% Japanese Capacitor, Flat Cables, ATX Power Supply Unit, UK Powercord, Black, Support Latest GPU'

Brand: MSI Product code: MPG A850GF

Product name: MPG A850GF UK PSU '850W, 80 Plus Gold certified, Fully Modular, 100% Japanese Capacitor, Flat Cables, ATX Power Supply Unit, UK Powercord, Black, Support Latest GPI!

- Supports the NVIDIA GeForce RTX $^{\text{\tiny{IM}}}$ 30 Series GPUs
- Full modular cable design
- Flat cable equipment
- 80 Plus Gold certified for high efficiency
- 100% all Japanese 105oC capacitor
- Active PFC design
- Industrial level protection with OVP,OCP,OPP,OTP, SCP,UVP
- LLC Half Bridge Topology with DC-DC module design

MSI MPG A850GF UK PSU '850W, 80 Plus Gold certified, Fully Modular, 100% Japanese Capacitor, Flat Cables, ATX Power Supply Unit, UK Powercord, Black, Support Latest GPU'






Power Ports & interfaces Forts (Express power connectors (6+2) pin) 6 AC input voltage* 100 - 240 V PCI Express power cable length 50 cm AC input frequency 47 - 63 Hz PCI Express power cable length 50 cm Maximum input current (@210V) 5 A PCPU power connector (24-pin) 4 Power Factor Correction (PFC) type Active Floppy disk drive cable length 110 cm Combined power (+13.V) 250 W PCI Express connector 4 Combined power (+53.W) 120 W PCI Express connector 4 Combined power (+13.W) 250 W PCI Express connector 4 Amax output current (+12V) 850 W PCI Express connector 4 Max output current (+12V) 40 A PVED Promance PUIJ-Modular Max output current (+12V1) 40 A Purpose* PC Max output current (+12V1) 40 A Purpose* PC Max output current (+12V1) 40 A Purpose* Power supply unit (PSU) form factor ATX Max output current (+12V1) 40 A Purpose*				
AC input voltage * 100 - 240 V pin) 6 6 6 6 6 7 - 63 Hz PCI Express power cable length 50 cm 50 cm 6 6 6 6 7 - 63 Hz CPU power connector (4+4 pin) 7 4	Power		Ports & interfaces	
Max output current (+3.3V) 22 A 80 Performance Max output current (+12V) 40 A Purpose * PC Max output current (+12V2) 40 A Power supply unit (PSU) form factor (PSU) form fa	AC input voltage * AC input frequency Maximum input current (@110V) Maximum input current (@220V) Power Factor Correction (PFC) type Combined power (+3.3V) Combined power (+12V) Combined power (+5V) Max output current (+3.3V) Max output current (+12V) Max output current (+12V1) Max output current (+12V2)	100 - 240 V 47 - 63 Hz 10 A 5 A Active 120 W 850 W 120 W 22 A 25 A 40 A	pin) PCI Express power cable length CPU power connector (4+4 pin) ATX Power connector (24-pin) Floppy disk drive connector Floppy disk drive cable length PCI Express connector	50 cm ✓ ✓ 110 cm
Max output current (+12V)			Performance	
Max output current (-12V) 0.3 A Country of origin China Max output current (+5Vsb) 2.5 A Design Image: Country of Origin Black Power protection features Over current, Over power, Over voltage, Short circuit, Under voltage Product colour Black Ports & interfaces Fan diameter 14 cm Motherboard power connector * 24-pin ATX On/off switch ✓ Motherboard power cable length 60 cm Weight & dimensions Number of SATA power cable length 950 mm Width 209 mm Peripheral (Molex) power cable length 950 mm Depth 287 mm Peripheral (Molex) power connector (4-pin) * 5 Height 129 mm EPS power connector (4+4 pin) ✓ Packaging data Package weight 3 kg EPS power connector (4-44 pin) Logistics data Logistics data 1 kg			80 PLUS certification * Purpose *	PC
Efficiency 90% Power protection features Over current, Over power, Over voltage, Short circuit, Under voltage Ports & interfaces Motherboard power connector * 24-pin ATX Motherboard power cable length Number of SATA power connectors 8 SATA power cable length Peripheral (Molex) power connectors (4-pin) * 5 EPS power connector (4+4 pin) EFS power connector (4+4 pin) Power are the final power of the service of the servic	•		Country of origin	China
Power protection features Over current, Over power, Over voltage, Short circuit, Under voltage Ports & interfaces Motherboard power connector * 24-pin ATX Motherboard power cable length Number of SATA power connectors 8 SATA power cable length Peripheral (Molex) power connectors (4-pin) * 5 EPS power connector (4+4 pin) Packaging data Over current, Over power, Over voltage Product colour Cooling type Active Active Active Fan diameter 14 cm Number of fans 1 fan(s) On/off switch Weight & dimensions Width 209 mm Depth 287 mm Height 129 mm Weight 3 kg Packaging data Package weight 3 kg Logistics data	Max output current (+5Vsb)	2.5 A	Design	
Ports & interfacesNumber of fans1 fan(s)Motherboard power connector * Motherboard power cable length Number of SATA power connectors SATA power cable length60 cmWeight & dimensionsNumber of SATA power connectors SATA power cable length950 mmWidth209 mmPeripheral (Molex) power connectors (4-pin) *5Height129 mmEPS power connector (4+4 pin)✓Weight3 kgPackaging data Package weight3 kgLogistics data	·	Over current, Over power, Over	Cooling type	Active
Motherboard power connector * Motherboard power cable length Number of SATA power connectors SATA power cable length Peripheral (Molex) power connectors (4-pin) *4Weight & dimensions Width209 mmEPS power connector (4+4 pin)5Depth287 mmEPS power connector (4+4 pin)✓Weight129 mmEPS power connector (4+4 pin)✓Weight3 kgPackaging data Package weight3 kgLogistics data	Ports & interfaces			
Number of SATA power connectors SATA power cable length Peripheral (Molex) power connectors (4-pin)* EPS power connector (4+4 pin) A Packaging data Package weight	•	24-pin ATX		
SATA power cable length 950 mm Width 209 mm Peripheral (Molex) power connectors (4-pin) * EPS power connector (4+4 pin) ** **Packaging data** Package weight **Depth 287 mm 129 mm ** **Packaging data** Package weight **Depth 287 mm **Packaging data** **Package weight **Depth 298 mm **Packaging data** **Package weight **Depth 299 mm **Packaging data** **Package weight **Package w	Number of SATA power connectors SATA power cable length Peripheral (Molex) power connectors (4-pin) *	8 950 mm 5	Weight & dimensions	
Package weight 3 kg Logistics data			Depth Height	287 mm 129 mm
Logistics data			Packaging data	
			Package weight	3 kg
Harmonized System (HS) code 84733020			Logistics data	
			Harmonized System (HS) code	84733020





824142225769

0824142225769



5715063368626

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.