



D-Link DAP-3712 wireless access point 867 Mbit/s White Power over Ethernet (PoE)

Brand : D-Link

Product code: DAP-3712

Product name : DAP-3712

- Features high-gain 23 dBi directional antenna supplying high-speed, stable coverage to up to 20 km away
 - Integrated TDMA Technology cuts through interference to ensure high-speed, consistent coverage
 - Superior throughput with single-band transfer speeds of up to 867 Mbps
 - Refined design effortlessly blends into any setting
 - Supports WPA2™ - Wi-Fi security for more protection
 - Support for Power over Ethernet means less wires, for cleaner and easier deployment
 - Features an IP66 rating, boasting water-resistant and dust-tight housings
- 20 km Long Range 802.11ac Wireless Bridge
 D-Link DAP-3712. 5 GHz, Maximum data transfer rate: 867 Mbit/s. Security algorithms: 128-bit AES.
 Ethernet LAN data rates: 100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White



Features		Power	
5 GHz *	✓	AC input voltage	48 V
Maximum data transfer rate *	867 Mbit/s	Power consumption (typical)	15 W
Maximum data transfer rate (5 GHz)	867 Mbit/s	Design	
Ethernet LAN data rates	100,1000 Mbit/s	Placement *	Pole
Frequency band	5.745 - 5.825 GHz	Product colour *	White
Bandwidth	0.08 GHz	Housing material	Acrylonitrile butadiene styrene (ABS)
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11n	International Protection (IP) code	IP66
Channels quantity	2 channels	Reset button	✓
Fit AP mode features	Wireless distribution system (WDS)	LED indicators	Signal strength
VLAN support	✓	Antenna	
Maximum outdoor range	20000 m	Antenna gain level (max)	23 dBi
Transmitting power (CE)	27 dBm	Certificates	
Security		Certification	CE, FCC
Security algorithms *	128-bit AES	Weight & dimensions	
MAC address filtering	✓	Width	372 mm
IP address filtering	✓	Depth	241 mm
Service Set Identifier (SSID) features	SSID broadcast	Height	372 mm
DHCP snooping	✓	Weight	900 g
Management features		Operational conditions	
Syslog	✓	Operating relative humidity (H-H)	0 - 90%
Firmware upgradeable	✓	Operating temperature (T-T)	-40 - 65 °C
Ports & interfaces		Storage temperature (T-T)	-40 - 85 °C
Ethernet LAN (RJ-45) ports *	1	Storage relative humidity (H-H)	0 - 90%
Power		Logistics data	
Power over Ethernet (PoE) *	✓	Harmonized System (HS) code	85176990



0790069461538



790069461538

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.