

CS1732_B / CS1734_B


2/4-Port USB 2.0 KVMP™ Switch with OSD

- The CS1732_B / CS1734_B are 2/4-port KVM switches combined with a 2-port USB 2.0 hub. As KVM switches, they allow users to access two or four computers from a single keyboard, monitor, and mouse console. There are four methods to obtain instant access to any computer in your installation: Pushbuttons, Hotkeys, OSD, and mouse.



Features

- 2/4-port KVMP switch with USB 2.0 support and 2.1 channel surround sound audio
 - One console controls 2 (CS1732_B) or 4 (CS1734_B) computers and two additional USB devices
 - 2-port USB 2.0 hub built in
 - USB 2.0 compliant
 - Dual interface – supports computers with PS/2 or USB keyboard and mouse configurations
 - Audio-enabled – full bass response provides a rich experience for 2.1 channel surround sounds systems
 - Console audio ports on front panel for easy access – ideal for IP phone use
 - Independent switching of KVM, USB, and Audio focus
 - Superior video quality; 2048 x 1536; DDC2B.
 - Supports widescreen resolutions
 - Computer selection via front panel pushbuttons, multilingual OSD (On Screen Display), hotkeys, and mouse
 - Multiplatform support – Windows, Mac, and Sun
 - Console mouse port emulation / bypass feature supports full mouse driver and multifunction mice
 - Video DynaSync™ – stores the console monitor's EDID (Extended Display Identification Data) to optimize display resolution
 - Complete keyboard emulation for error free booting
 - Sun/Mac keyboard support and emulation*
 - Auto Scan Mode for monitoring all computers
 - LED display for easy status monitoring
 - Easy installation – no software required
 - Firmware upgradeable
- *1.PC keyboard combinations emulate Sun/Mac keyboards
 2.Sun/Mac keyboards only work with their own computers



Specification

Function		CS1732 _B	CS1734 _B	
Computer Connections		2	4	
Port Selection		OSD; Hotkey; Pushbutton; Mouse		
Connectors	Console Ports	Keyboard	1 x USB Type A Female (Black)	
		Video	1 x HDB-15 Female (Blue)	
		Mouse	1 x USB Type A Female (Black)	
		Speaker	2 x Mini Stereo Jack Female (Green)	
		Mic.	2 x Mini Stereo Jack Female (Pink)	
	KVM Ports	Keyboard	2 x SPHD-15 Female (Yellow)	4 x SPHD-15 Female (Yellow)
		Video		
		Mouse		
		Speaker	2 x Mini Stereo Jack Female (Green)	4 x Mini Stereo Jack Female (Green)
		Mic.	2 x Mini Stereo Jack Female (Pink)	4 x Mini Stereo Jack Female (Pink)
FW Upgrade		1 x 4-conductor 3.5mm Jack (Black)		
Power		1 x DC Jack		
USB Hub		2 x USB Type A Female (White)		
Switches	Selected	2 x Pushbutton	4 x Pushbutton	
LEDs	On Line / Selected	2 (Orange)	4 (Orange)	
	USB Link	2 (Green)	4 (Green)	
Emulation	Keyboard / Mouse	PS/2; USB		
Video		2048 x 1536 @ 60Hz; DDC2B		
Scan Interval		1-255 seconds (Default: 5 sec.)		
Power Consumption		DC5.3V, 3.1W	DC5.3V, 3.4W	
Environment	Operating Temp.	0-50°C		
	Storage Temp.	-20-60°C		
	Humidity	0-80% RH, Non-condensing		
Physical Properties	Housing	Metal		
	Weight	0.55 kg	0.78 kg	
	Dimensions (L x W x H)	13.98x8.80x5.55cm	21.00x8.80x5.55cm	

