

USB-A to Lightning Sync/Charge Coiled Cable (M/M) - MFi Certified, Black, 4 ft. (1.2 m)

MODEL NUMBER: M100-004COIL-BK



Charges and synchronizes your Apple iPhone, iPad or iPod using the USB port on your computer or wall/car charger.

Features

Helps You Charge and Sync Your Apple Mobile Device

The M100-004COIL-BK connects your iPhone, iPad or iPod to the USB-A port on a computer or USB charger, so you can charge your Apple device and transfer data simultaneously. The reversible 8-pin Lightning plug connects in either direction to ensure fast, easy connection every time. The charging cable is MFi-certified for broad compatibility with iPhone, iPad and iPod devices.

Coiled to Take Up Less Space

The four-foot cord is coiled to take up less space than a standard sync/charge cable. It helps avoid cable clutter on your desktop, resists tangles and is easier to carry in your purse, backpack or briefcase. The cable has an effective length of two to three feet (0.6 to 0.9 meters) when in use.

Specifications

| OVERVIEW | |
|--|---------------------------------|
| UPC Code | 037332192110 |
| Technology | Lightning; USB 2.0 (High Speed) |
| Cable Type | Passive |
| INPUT | |
| Maximum Input Amps | 2 |
| POWER | |
| USB Power Delivery (PD) Charging Support | No |

Highlights

- 4 ft. cable is coiled to take up less space and avoid cord clutter
- Effective length of 2 to 3 ft. when in use
- Reversible Lightning plug compatible with all devices with 8-pin connectors
- USB plug connects to USB-A port on computer or charger
- MFi-certified for use with iPhone, iPad and iPod devices

System Requirements

- Device or charger with USB-A port
- Most current iPhone, iPad and iPod devices

Package Includes

M100-006-BK USB-A to Lightning Sync/Charge Coiled Cable (M/M), Black, 4 ft. (1.2 m)



Powering Business Worldwide

TRIPP LITE
SERIES

| CHARGING | |
|---------------------------------------|------------------------------|
| Total Charging Watts | 12 |
| PHYSICAL | |
| Material of Construction | PU, PVC |
| Cable Jacket Color | Black |
| Cable Jacket Material | PVC |
| Cable Jacket Rating | VW-1 |
| Cable Outer Diameter (OD) | 3.8mm |
| Wire Gauge (AWG) | 28/22 |
| Cable Length (ft.) | 4 |
| Cable Length (m) | 1.22 |
| Cable Length (in.) | 48 |
| Shipping Dimensions (hwd / in.) | 4.57 x 2.40 x 0.91 |
| Shipping Dimensions (hwd / cm) | 11.61 x 6.10 x 2.31 |
| Shipping Weight (lbs.) | 0.05 |
| Shipping Weight (kg) | 0.02 |
| Unit Dimensions (hwd / in.) | 0.000 x 0.000 x 0.000 |
| Unit Packaging Type | Box |
| ENVIRONMENTAL | |
| Operating Temperature Range | -4° to 140°F (-20° to 60°C) |
| Storage Temperature Range | -4° to 140°F (-20° to 60°C) |
| Operating Humidity Range | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range | 0% to 90% RH, Non-Condensing |
| Power Provided to Connected Device(s) | 12W (5V/2.4A) |
| CONNECTIONS | |
| Side A - Connector 1 | USB A (MALE) |
| Side B - Connector 1 | LIGHTNING (MALE) |
| Connector Plating | Nickel |
| Contact Plating | Gold |
| Connector Style | Straight |
| FEATURES & SPECIFICATIONS | |
| USB Specification | USB 2.0 (up to 480 Mbps) |



Powering Business Worldwide

TRIPP LITE
SERIES

| | |
|-------------------------------------|-------------------------|
| Data Transfer Rate | 480 Mbps |
| Angled Plug | No |
| STANDARDS & COMPLIANCE | |
| Product Certifications | MFi |
| Product Compliance | RoHS; REACH; UKCA |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.