



XPG SX8200 Pro PCI e Gen3x4 M.2 2280 Solid State Drive

The SX8200 Pro M.2 2280 SSD is XPG's fastest SSD to date and is designed for avid PC enthusiasts, gamers, and overclockers. It features an ultra-fast PCIe Gen3x4 interface that offers peak read/write speeds of 3500/3000MB per second, outpacing SATA 6Gb/s by a wide margin. Supporting NVMe 1.3, the SX8200 Pro delivers excellent random read/write performance and multi-tasking capabilities. With SLC caching, a DRAM Cache buffer, E2E Data Protection, and LDPC ECC, it maintains high speeds and data integrity, even during highly intensive applications such as gaming rendering, and overclocking.

Features

- Ultra-fast PCIe Gen3x4 interface:
 R/W speed up to 3500/3000MB/s
- NVMe 1.3 support
- 3D NAND Flash for higher capacity and durability
- Advanced LDPC ECC Technology
- SLC Caching and DRAM cache buffer
- E2E Data Protection and RAID Engine
- Compact M.2 2280 form factor ideal for gaming and high-end desktops

Ordering Information

Capacity	Model Number	EAN Code			
256GB	ASX8200PNP-256GT-C	4713218469441			
512GB	ASX8200PNP-512GT-C	4713218469458			
1TB	ASX8200PNP-1TT-C	4713218469465			



Specifications

• Capacities: 256GB / 512GB / 1TB

• NAND Flash: 3D TLC

Interface: PCIe Gen3x4Form Factor: M.2 2280

• MTBF: 2,000,000 hours

• Dimensions (L x W x T): 22 x 80 x 3.5mm

• Weight: 8g

• Power Consumption: 0.33W Active (Typical),

0.14W Slumber (Typical) (*measured by power meter)

• Operating Temperature: 0°C~70°C

 \bullet Storage Temperature: -40°C~85°C

• Shock Resistance: 1500G/0.5ms

• Certifications: RoHS, CE, FCC, BSMI, VCCI, KC

• Warranty: 5 years

Performance

Capacity	ATTO Seq. Read (MB/sec)	ATTO	CDM	CDM	AS SSD	AS SSD	4K	4K	
		Seq.	(QD32)	(QD32)	Seq.	Seq.	Random	Random	TBW
		Write	Seq. Read	Seq. Write	Read	Write	Read	Write	
		(MB/sec)	(MB/sec)	(MB/sec)	(MB/sec)	(MB/sec)	IOPS	IOPS	
256GB	3350	1150	3500	1200	2950	1100	220K	290K	160TB
512GB	3350	2350	3500	2300	3000	2100	390K	380K	320TB
1TB	3350	2800	3500	3000	3000	2500	390K	380K	640TB

^{*}Performance may vary based on SSD capacity, hardware test platform, test software, operating system and other system variables

Schematics

