

HO 325 PTB **32"** Open Frame Touch Monitor

Experts in **Display**

Open Frame Touch Monitor

HO 325 PTB 31.5" / 80cm Diagonal LED Backlight – Format 16:9

- 1920 x 1080 Full HD 1080P Resolution
- 10-Point Touch P-Cap Technology
- 178° / 178° Ultra Wide Viewing Angle
- 400 cd/m² High Brightness Panel
- Video Input: HDMI + Display Port
- IP55 (front) Rating Level
- Display Protection: Thickness 3mm
- Built-in Speakers
- ≥7H Toughened Hard Panel Surface
- Slim Profile, Edge-to-Edge True Flat Surface
- Metal chassis, frame and back cover
- VESA Mount and Multiple Mounting Options
- Edge to Edge glass without raised frame
- Orientation: Landscape, Portrait, Face-Up









31.5" / 80 cm

Part. No..: HO 325 PTB

SIZE, RESOLUTION



32"

16:9 Aspect Ratio



Full HD 1920 x 1080

CONNECTIVITY, IP LEVEL



HDMI DP



IP 55 Water & Dust Protection

VIEWING ANGLE, VESA



178 Ultra-Wide Viewing Angle



VESA Mount

OTHER FEATURES



10 Point Touch



30.000 Hours Lifetime

Display Solutions



HO 325 PTB **32"** Open Frame Touch Monitor

Experts in **Display**

Display Size	80 cm / 31.5" Diagonal		
Panel Type	TFT – LED Backlight		
Aspect Ratio	16:9		
Resolution (H x V)	1920 x 1080 Full HD		
Brightness (Typ.)	400cd/m² Panel / 340 cd/m² Monitor		
Contrast (Typ.)	1.200:1 (Typical) / 10.000.000:1 (Active)		
Display Area	698,4 x 392,85 mm		
Viewing Angle L/R; U/D	178° H / 178° V (CR > 10)		
Response Time	8 msec		
Pixel Pitch	0,364 (H) x 0,364 (V) mm		
Touch Type	Projected Capacitive Type – 10 Point Touch Material Glass + Glass (OGS+CG).		
Display Colors	16.7M Colors		
Horizontal Frequency	31 ~ 83 kHz		
Vertical Frequency	56 ~ 75 Hz		
Max Display Frequency	1920 x 1080 @ 60Hz		
Input 1	HDMI		
Input 2	Display Port		
Input 3	USB Type B (Touch)		
Speakers	Yes, 2W x 2, Earphone output		
Power Consumption	On: 40W; Stand-by: 0.257W; Off: 0.235W		
AC Power Range	AC 100 ~ 240 Volt; 50 ~ 60 Hz		
Product Dimensions	747 x 64.3 x 451.4 mm (W x D x H)		
Packing Dimensions	863 x 163 x 577 mm (W x D x H)		
Net / Gross Weight	14,5 Kg / 16,8 Kg		

VESA Mounting	100 x 100 mm. VESA Screws: M6, 10mm (Max), pitch 1 Rear Cover Screws: M4, 10mm (Max), pitch 0.7		
Display Protection	Thickness 3±0.3 mm		
Hardness / Transmittance	≥7H Toughened hard panel surface / ≥86%		
IP Rating Level	IP 55 on surface (Front), Dust and Water Protection *		
Controls	Menu, Up, Down, Bri (+), Vol (-), Input/Return, Power		
LED Backlight life	30.000 hours		
Accessory	EU and UK Power cables; HDMI Cable (1.5m); USB Cable for Touch (1,8m); Quick Start Guide, Warranty Card		
Certifications	CE, RoHS, EU Energy Label		
On Screen Display	15 Languages		
Color	Warm, Nature, Cool, User's Mode		
Preset Mode	PC, Movie, Game, ECO Modes		
Housing	Material: Sheet Metal, Color: Black		
Orientation	Landscape, Portrait, Face-Up		

H/		espoid evep	G 900 	1981
A	(++ (+		A	
6 6	ľ			_
ENE ENE ENE		GIIA IE	59 Wh/annur	
	80,1	40 Vatt	31.5 inch	" ")
201	0/1062 - 2	017		

Supplier's Name	HANNspree	
Model Name	HO325PTB	
Energy Efficiency Class	А	
Screen Size (Centimetres)	80.0	
Screen Size (Inches)	31.5	
On mode power Consumption (W)	40	
Annual Energy Consumption* (kWh)	59	
Standby-mode Power Consumption (W)	0,26	
Off-mode Power Consumption (W)	0,24	
Screen Resolution	1920 x 1080	

PART. NO.: HO 325 PTB



^{© 2020} HANNSpree Europe Holdings B.V. Specifications and design as well as accessories are subject to change without notice. Screen shots are simulated. Actual products may differ slightly from those illustrated on this promotion material. Please refer to actual samples for final selection. The products displayed on this promotion material may not be available for purchase in your particular country or locality. Please check with your local HANNspree authorized representatives for the availability of specific products in your area. All brand, product, Service names and logos are trademarks and/or registered trademarks of their respective manufactures and Companies.

^{*} IP55: The IP Code classifies how resistant a device is to foreign objects and moisture.

IP55 means that the monitor is protected from dust and can operate in dusty conditions. It is also protected against water jets projected by a nozzle (6.3mm) from any direction.



HO 325 PTB **32"** Open Frame Touch Monitor

Experts in **Display**



