

AXIS TA4702 Key Fob

Secure and robust physical access

Contactless MIFARE[®] DESFire[®] EV2 2K key fob that uses advanced radio frequency identification (RFID) technology to deliver secure and reliable physical access to premises. The key fob is made of impact-resistant matt polycarbonate and ultrasonically welded in a stainless steel frame, making it stable and durable, with IP67 and IK09 rating – perfect for carrying on a keyring. One bulk pack comes with 50 key fobs.

- > [MIFARE[®] DESFire[®] EV2](#)
- > [Ultrasonically welded stainless steel frame](#)
- > [IP67- and IK09-rated](#)
- > [Small and thin keyfob](#)



AXIS TA4702 Key Fob

General	
Material	Plastic and stainless steel Color: black
Sustainability	PVC free
Quantity	50 pcs
Dimensions	47.3 x 35 x 4.5 mm (1.86 x 1.38 x 0.18 in)
Weight	359 g (12.7 oz)
Memory	2 kB Encoding: 500 000 cycles Retention time: 25 years
Electronics	RFID frequency: 13.56 MHz (HF) Chip type: NXP Mifare® DESFire® EV2
Operating conditions	-25 °C to 70 °C (-13 °F to 158 °F)
Storage conditions	-25 °C to 50 °C (-13 °F to 122 °F) Humidity 20-90% RH
Approvals	Environment IEC/EN 60529 IP67, IEC/EN 62262 IK09, ISO 21207 method B, IEC 60068-2-31 RFID ISO 14443A
Warranty	5-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility