

ViewSonic® LCD DISPLAY VX3219-PC-MHD

Key Features

- 240Hz refresh rate for smooth gameplay
- 1ms (MPRT) response time for precision
- 1500R Curved screen for immersive visuals
- Adaptive™ Sync prevents screen tearing
- Full HD resolution for rich detail



Product Description

Upgrade your PC experience with the 32" VX3219-PC-MHD. The large display features a 1500R curve for truly immersive gameplay and the ultra-responsive 240Hz display provides pro-level refresh rates, so you can stay ahead of the competition and enjoy ultra-smooth gaming no matter how intense the action gets. A clean design, with 3-side borderless display and sleek dimensions create a product that delivers all you need. Adaptive™ Sync technology virtually eliminates screen tearing and stuttering for a fluid gaming experience. And the 1ms MPRT response time enables you to react in-game with complete precision, removing ghosting and motion blur. VX3219-PC-MHD is also equipped with ViewSonic's exclusive ViewMode™ presets, which offer optimized screen performance for a variety of needs, such as gaming, editing, or watching movies. In addition, a DisplayPort and HDMI inputs offer flexible connectivity for gaming and entertainment.

Visit Us — www.viewsonic.com

DISPLAY

Display Size (in.):	32
Viewable Area (in.):	31.5
Panel Type:	VA Technology
Resolution:	1920 x 1080
Resolution Type:	FHD
Static Contrast Ratio:	4,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	300 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (MPRT):	1ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	1500R
Refresh Rate (Hz):	240
Adaptive Sync:	Yes
Blue Light Filter:	Yes
Flicker-Free:	Yes

Color Gamut:	NTSC: 72% size (Typ) sRGB: 103% size (Typ)
Pixel Size:	0.364 mm (H) x 0.364 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

3.5mm Audio Out:	1
HDMI 2.0:	2
DisplayPort:	1
Power in:	External power adapter

AUDIO

Internal Speakers:	2Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	25W
Eco Mode (optimized):	31W
Consumption (typical):	37W
Consumption (max):	40W
Voltage:	AC 100-240V, 50/60 Hz
Stand-by:	0.5W
Power Supply:	External

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	HDMI (v2.0): 31.469 ~ 291.309KHz, DisplayPort (v1.2): 31.469 ~ 219.309KHz
Frequency Vertical:	HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.2): 48 ~ 240Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2)
---------------	--

ERGONOMICS

Tilt (Forward/Back):	-5° / 20°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	10.8
Net Without Stand (lbs):	9.3
Gross (lbs):	15.4

WEIGHT (METRIC)

Net (kg):	4.9
Net Without Stand (kg):	4.2
Gross (kg):	7

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	38.2 x 20.6 x 6.7
Physical (in.):	27.9 x 20.2 x 9
Physical Without Stand (in.):	27.9 x 16.5 x 3.7

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	970 x 523 x 170
Physical (mm):	709 x 513 x 228
Physical Without Stand (mm):	709 x 419 x 93

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS
PACKAGE CONTENTS:	VX3219-PC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Country Of Origin:	28