




StarTech.com IDE to SATA Hard Drive or Optical Drive Adapter - 40-Pin PATA to 2.5" SATA HDD/SSD/ODD Converter

Brand : StarTech.com

Product code: IDE2SAT2

Product name : IDE to SATA Hard Drive or Optical Drive Adapter - 40-Pin PATA to 2.5" SATA HDD/SSD/ODD Converter



StarTech.com IDE to SATA Hard Drive or Optical Drive Adapter Converter - 40-Pin PATA to 2.5" SATA HDD / SSD / ODD Converter

[StarTech.com IDE to SATA Hard Drive or Optical Drive Adapter - 40-Pin PATA to 2.5" SATA HDD/SSD/ODD Converter:](#)

Connect your SATA Hard Drive or Blu-ray/DVD/CD-ROM Drive to an IDE motherboard

The IDE2SAT2 40-pin IDE to SATA adapter enables you to connect a SATA I/II/III drive to an available IDE/ATA 33/66/100/133 motherboard port - a cost effective solution that allows you to add newer SATA drives, and keep your existing motherboard.



The IDE/SATA adapter offers a cost-effective solution for bridging the gap between a newer 2.5"/3.5"/5.25" SATA drive and older IDE motherboard port. The IDE2SAT2 also features ODD (Optical Disk Drive) support, allowing you to add Blu-ray, DVD, or CD-ROM drives to an older IDE motherboard.

The IDE/SATA adapter is backed by a StarTech.com 2-year Warranty and free lifetime technical support.

The StarTech.com Advantage



Ports & interfaces		Weight & dimensions	
Host interface *	IDE	Width	20 mm
Output interface *	SATA	Depth	75.5 mm
Connector(s)	1 x IDE (40 Pin; EIDE/PATA), 1 x SATA (7+15 pin), 1 x SP4 (4 pin)	Height	23 mm
		Weight	29 g
Design		Packaging data	
Internal *	✓	Manual	✓
Product colour	Red	Package width	175 mm
Certification	FCC, CE, TAA, REACH	Package depth	145 mm
		Package height	33 mm
		Package weight	89 g
Features		Logistics data	
Chipset	Marvell - 88SA8052	Harmonized System (HS) code	84733020
Data transfer rate (max)	0.133 Gbit/s	Products per master (outer) case	60 pc(s)
Logical block addressing (LBA) support	48 bit	Master (outer) case width	380 mm
		Master (outer) case length	496 mm
		Master (outer) case height	321 mm
Operational conditions		Other features	
Operating temperature (T-T)	5 - 50 °C	Material	Plastic, Steel
Storage temperature (T-T)	-25 - 80 °C		
Operating relative humidity (H-H)	15 - 90%		
Technical details			
Compliance certificates	RoHS		



0065030852258



065030852258



0780727856622



780727856622

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.