StarTech.com

StarTech.com 2 Port USB HDMI Cable KVM Switch with Audio and Remote Switch – USB Powered

Brand : StarTech.com

Product code: SV211HDUA

Product name : 2 Port USB HDMI Cable KVM Switch with Audio and Remote Switch – USB Powered

StarTech.com 2 Port USB HDMI Cable KVM Switch with Audio and Remote Switch - USB Powered KVM with HDMI - Dual Port HDMI KVM Switch
StarTech.com 2 Port USB HDMI Cable KVM Switch with Audio and Remote Switch – USB Powered. Keyboard port type: USB, Mouse port type: USB, Video port type: HDMI. Maximum resolution: 1920 x 1200 pixels, Maximum digital resolution: 1920 x 1200 pixels. Product colour: Black, Housing material: Plastic, Cable length: 0.85 m. Windows operating systems supported: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Mac operating systems supported: Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Server operating systems supported: Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows.... Compliance certificates: RoHS

Ports & interfaces	
Number of computers controlled *	2
Keyboard port type *	USB
Mouse port type *	USB
Video port type *	HDMI
Console ports *	3.5mm headphone, 3.5mm mic, HDMI, USB A
Console USB ports quantity	2
Audio connections	✔

Network	
Ethernet LAN	✖

Performance	
Maximum resolution *	1920 x 1200 pixels
Maximum digital resolution	1920 x 1200 pixels
HDCP	✔
Hot-Plug support	✔
Daisy chain	✖

Design	
Rack mounting *	✖
Product colour *	Black
Housing material	Plastic
Cable length	0.85 m
LED indicators	✔
Certification	FCC, CE, REACH

Display	
Built-in display *	✖

Power	
USB powered	✔

System requirements

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019

Sustainability

Compliance certificates	RoHS

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 90%

Weight & dimensions

Width	66 mm
Depth	88 mm
Height	23 mm
Weight	350 g

Packaging data

Package width	161 mm
Package depth	250 mm
Package height	62 mm
Package weight	464 g

Packaging content

Manual	✔
Software included	✔

Other features

Audio support	✔

Other features	
IP control	✖
Logistics data	
Harmonized System (HS) code	85176200

0065030851060

065030851060

5054533527652