

Canon imageFORMULA P-208II Sheet-fed scanner 600 x 600 DPI A4

Brand : Canon Product family: Product code: 9704B003

imageFORMULA

Product name: P-208II

600x600DPI, LED, 216x356mm, USB 2.0, 600g, black

Canon imageFORMULA P-208II. Maximum scan size: 216 x 356 mm, Optical scanning resolution: 600 x 600 DPI, Input colour depth: 24 bit. Scanner type: Sheet-fed scanner, Product colour: Black. Sensor type: CIS, Light source: LED, Scan drivers: ISIS, TWAIN. Standard input capacity: 1 sheets. Maximum ISO Aseries paper size: A4, Scanning media types supported: Business Card, Card stock, Plain paper, Post Card(JPN), ISO A-series sizes (A0...A9): A4









Scanning		Paper handling	
Maximum scan size * Optical scanning resolution * Colour scanning Duplex scanning * Input colour depth Film scanning Greyscale levels ADF scan speed (b/w, A4) ADF scan speed (colour, A4) Duplex ADF scan speed (b/w, A4) Duplex ADF scan speed (colour, A4) Black/white scanning colour modes	•	Auto Document Feeder (ADF) media weight Maximum scan area (ADF) Minimum scan area (ADF)	52 - 380 g/m ² 216 x 356 mm 50.8 x 70 mm
		Ports & interfaces	
		USB port * USB version Standard interfaces	2.0 USB 2.0
		Power	
		Power supply type * Power consumption (typical) Power consumption (standby)	USB 2.5 W 1.5 W
Design		Power consumption (off)	0.1 W
Scanner type *	Sheet-fed scanner	Current	0.5 A
Product colour * Built-in display *	Black X	Weight & dimensions	
Performance		Width Depth	312.5 mm 89.5 mm
Sensor type * Light source Scan drivers	CIS LED ISIS, TWAIN	Height Weight	40 mm 600 g
	ISIS, I WAIIV	Sustainability	
Input capacity Standard input capacity	1 sheets	Sustainability certificates	ENERGY STAR
	1 Sileets	System requirements	
Paper handling Scanning media types supported	Business Card, Card stock, Plain paper, Post Card(JPN)	Windows operating systems supported Mac operating systems supported	1
Maximum ISO A-series paper size *	A4	Operational conditions	•
ISO A-series sizes (A0A9)	A4	Operational conditions Operating temperature (T-T)	10 - 32.5 °C
Letter	√	Operating relative humidity (H-H)	25 - 80%
		Other features	
		Compliance certificates	RoHS
		Logistics data	
		Harmonized System (HS) code	84716070





4528472106366

4053162871083



4528472106359

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.