



## Lindy 2m DisplayPort 1.2 Cable, Black Line

**Brand :** Lindy

**Product code:** 36492

**Product name :** 2m DisplayPort 1.2 Cable, Black Line

2m DisplayPort 1.2 Cable, Black Line

[Lindy 2m DisplayPort 1.2 Cable, Black Line:](#)

From the Lines cable connectivity concept developed by Lindy, Black Line DisplayPort cables are fully featured, entry level high resolution connection solutions, perfect for home and small office use.

Black Line DisplayPort cables feature triple shielded construction with 30AWG copper conductors for performance and corrosion resistance. Nickel connectors and 24K gold plated contacts maintain signal integrity and reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit are supported. Black Line DisplayPort cables are also capable of transmitting 32 channel audio and Dolby® True HD. Black Line DisplayPort cables are capable of delivering 4:4:4 colour spacing for the most accurate colour representation possible.

Black Line DisplayPort cables are available in lengths from 0.5m to 3m.



Features		Features	
Connector 1 form factor	Straight	Connector material	Nickel
Connector 2 form factor	Straight	Plug and Play	✓
Connector contacts plating	Gold	Bend radius (min)	4.8 cm
DisplayPort version	1.2	Colour sampling	4:4:4
Maximum resolution *	4096 x 2160 pixels	Cable type	Round cable
Supported graphics resolutions	4096 x 2160	Nominal attenuation	300kHz-825MHz - 5dB, 825MHz-2.475GHz - 5dB, 2.475GHz-4.125GHz - 12dB, 4.125GHz-5.1GHz - 20dB
Maximum refresh rate	60 Hz	Certification	RoHS, REACH, UL
Cable length *	2 m	<b>Operational conditions</b>	
Connector 1 *	DisplayPort	Operating temperature (T-T)	-20 - 80 °C
Connector 2 *	DisplayPort	Storage temperature (T-T)	-25 - 85 °C
Connector 1 gender *	Male	<b>Packaging data</b>	
Connector 2 gender *	Male	Cable diameter	6 mm
Product colour *	Black	Connector 1 dimensions (WxDxH)	21 x 38.9 x 13.6 mm
Cable material	Copper	Connector 2 dimensions (WxDxH)	21 x 38.9 x 13.6 mm
Cable shielding	Copper	Quantity per pack	1 pc(s)
Jacket material	Polyvinyl chloride (PVC)	Package type	Polybag
Connector housing material	Acrylonitrile butadiene styrene (ABS)	<b>Logistics data</b>	
AWG wire size	30	Harmonized System (HS) code	84733080
Data transfer rate	21.6 Gbit/s		
Contact material	Phosphor bronze		



4002888364928

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-NOV-2024. Prints or copies of Information are only valid on the printed Publication date