




TP-Link AC1200 Mesh Wi-Fi Extender

Brand : TP-Link

Product code: RE330

Product name : AC1200 Mesh Wi-Fi Extender

- Eliminate weak signal areas with whole home WiFi coverage
 - 2.4 GHz (300 Mbps) and 5 GHz (867 Mbps) dual-band WiFi connection ensures more stable wireless experience
 - Creates a Mesh network by connecting to a OneMesh router for seamless whole-home coverage
 - Adaptive Path Selection – connects to the fastest connection path to the router automatically and runs at top-speed
 - High Speed Mode – maximizes speed by using one WiFi band as dedicated backhaul, ideal for HD streaming and gaming
 - AP Mode – create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability
 - Smart signal indicator helps to find the best location for optimal Wi-Fi coverage by showing the signal strength
 - Push the WPS button to easily connect to the router and you can uniformly manage from the Tether app or Web UI
 - Works with any Wi-Fi router or wireless access point
- 1 x 10/100M Ethernet Port (RJ45), IEEE 802.11a/n/ac 5 GHz, IEEE 802.11b/g/n 2.4 GHz, 69.5×35.0×124.1 mm



| Performance | | Design | |
|----------------------------|---|-----------------------------|----------|
| Type * | Network repeater | Product colour | White |
| Data transfer rate | 867 Mbit/s | LED indicators | ✓ |
| Ethernet LAN data rates | 10,100 Mbit/s | Quantity per pack | 1 pc(s) |
| Antenna | | Power | |
| Antennas quantity | 2 | Power consumption (typical) | 9.5 W |
| Antenna type | Internal | Weight & dimensions | |
| Network | | Width | 69.5 mm |
| Cabling technology | 10/100Base-T(X) | Depth | 35 mm |
| Networking standards | IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n | Height | 124.1 mm |
| Wi-Fi | ✓ | Packaging content | |
| Wi-Fi standards | 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac) | Manual | ✓ |
| Wi-Fi data rate (max) | 867 Mbit/s | Packaging data | |
| Wi-Fi band | Dual-band (2.4 GHz / 5 GHz) | Package type | Box |
| Security algorithms | 64-bit WEP, 128-bit WEP, WPA-PSK, WPA2-PSK | Logistics data | |
| Ports & interfaces | | Harmonized System (HS) code | 85176990 |
| Ethernet LAN (RJ-45) ports | 1 | | |



4897098682685



0840030703034



840030703034



4897098683033

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.