

DELL P Series 22 Monitor - P2222H Without Stand

Brand : DELL **Product family:** P Series **Product code:** DELL-P222HWOS

Product name: Dell 22 Monitor - P2222H Without Stand

- 54.6cm (21.5") Full HD 1920 x 1080 LED IPS
- 8ms, 16:9, 250cd/m², 1000:1
- USB, VGA, HDMI, DisplayPort

Display diagonal (metric)

54.61 cm

 $54.6 cm~(21.5")~Full~HD~1920~x~1080~LED~IPS,~16:9,~250 cd/m^2,~16.7 M,~8 ms,~178°/178°,~1000:1180~Ms,~1000:1180~$

DELL P Series 22 Monitor - P2222H Without Stand:

Stay productive no matter where you work. Reduce harmful blue light with this sleek 21.5-inch FHD monitor featuring ComfortView Plus technology.

DELL P Series 22 Monitor - P2222H Without Stand. Display diagonal: 54.6 cm (21.5"), Display resolution: 1920×1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178° , Viewing angle, vertical: 178° . Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting. Product colour: Black











Display		Ergonomics	
Display diagonal *	54.6 cm (21.5")	Swivelling	×
Display resolution *	1920 x 1080 pixels	Tilt adjustment	×
HD type *	Full HD	Tilt angle range	0 - 0°
Native aspect ratio *	16:9	On Screen Display (OSD)	✓
Display technology *	LCD	Plug and Play	✓
Panel type *	IPS	LED indicators	Power
Backlight type	LED	Power	
Touchscreen *	×	Energy efficiency class (SDR) *	D
Display brightness (typical)	250 cd/m ²	Energy efficiency class (HDR) *	Not available
Response time *	8 ms	Energy consumption (SDR) per 1000	1
Anti-glare screen	✓	hours *	, 12 kWh
Screen shape *	Flat	Power consumption (typical) *	11.8 W
Supported graphics resolutions	1920 x 1080 (HD 1080)	Power consumption (standby) *	0.3 W
Supported video modes	480p, 576p, 720p, 1080i, 1080p	Power consumption (max)	46 W
Aspect ratio	16:9	Power consumption (off)	0.2 W
Contrast ratio (typical) *	1000:1	AC input voltage	100 - 240 V
Maximum refresh rate *	60 Hz	AC input frequency	50 - 60 Hz
Viewing angle, horizontal	178°	Power supply type	Internal
Viewing angle, vertical	178°	Energy efficiency scale	A to G
Display number of colours *	16.7 million colours	European Product Registry for	549695
Response time (fast)	5 ms	Energy Labelling (EPREL) code	349093
Pixel pitch	0.248 x 0.248 mm	Operational conditions	
Pixel density	102 ppi	Operating temperature (T-T)	0 - 40 °C
Horizontal scan range	30 - 83 kHz	Storage temperature (T-T)	-20 - 60 °C
Vertical scan range	56 - 76 Hz	Operating relative humidity (H-H)	10 - 80%
Viewable size, horizontal	47.6 cm	Storage relative humidity (H-H)	5 - 90%
Viewable size, vertical	26.8 cm	Operating altitude	0 - 5000 m
Viewable size diagonal	54.6 cm	Non-operating altitude	0 - 12192 m
Display diagonal (metric)	54.61 cm	sperating dicitade	JJE !!!

Display		Weight & dimensions	
High Dynamic Range (HDR) supported sRGB coverage (typical)	× 99%	Width (with stand) Width (without stand) Depth (without stand)	487.3 mm 487.3 mm 52.1 mm
Performance		Height (without stand)	290 mm
Flicker-free technology Low Blue Light technology	√	Weight (without stand) Bezel width (side) Bezel width (top)	2.82 kg 5.6 mm 5.6 mm
Multimedia		Bezel width (bottom)	1.66 cm
Built-in speaker(s) * Built-in camera *	×	Packaging content	AC Division But HBMI HCD VCA
Design		Cables included Quick start guide	AC, DisplayPort, HDMI, USB, VGA ✓
Market positioning * Product colour *	Business Black	Sustainability	•
Front bezel colour	Black	Sustainability certificates Doesn't contain	ENERGY STAR, EPEAT Gold PVC/BFR
Ports & interfaces		Carbon footprint	
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity VGA (D-Sub) ports quantity HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Headphone out * HDCP	3.2 Gen 1 (3.1 Gen 1) USB Type-B 1 4 1 1 1.4 1 1.2 X	Total carbon footprint (kg of CO2e) Total carbon emissions, standard deviation (kg of CO2e) Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) Other features	463 106 325 23 113 1
Network	•	Heavy metals free	Hg (mercury)
Wi-Fi	×	Compliance certificates	RoHS
	^	Logistics data	
VESA mounting * Panel mounting interface Cable lock slot * Height adjustment * Pivot	100 x 100 mm X X	Harmonized System (HS) code	85285210





5397184505151

5715063497760

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.