



## ATEN 4K Active DisplayPort to HDMI converter, 3D, up 3840 by 2160 @30Hz

**Brand :** ATEN

**Product code:** VC986-AT

**Product name :** 4K Active DisplayPort to HDMI converter, 3D, up 3840 by 2160 @30Hz



4K DisplayPort to HDMI Active Adapter

ATEN 4K Active DisplayPort to HDMI converter, 3D, up 3840 by 2160 @30Hz:

### Plug-n-Play

No installation software or drivers required. The VC986 is the perfect solution for connecting DisplayPort inputs to HDMI output displays. The built-in chip ensures high quality signal conversion, smooth output, and compatibility with DP++.

### Supports 4K

Supports resolutions up to 4K, making it highly compatible across devices.

### Superior Signal Quality

The internal copper foil shielding protection ensures signal integrity and minimizes external interference, giving you extra reliable and superior quality signals.

### AMD Eyefinity Compatible

Compatible with AMD Eyefinity graphics cards for multiple display applications.

### Package Contents

1x VC986 4K DisplayPort to HDMI Active Adapter



Features		Weight & dimensions	
Connector 1 form factor	Straight	Weight	100 g
Connector 2 form factor	Straight	Width	45 mm
Connector 1 *	DisplayPort	Depth	180 mm
Connector 2 *	HDMI	Height	15 mm
Connector 1 gender *	Male	<b>Packaging data</b>	
Connector 2 gender *	Female	Quantity per pack	1 pc(s)
HDCP	✓	Package width	19 mm
HDCP version	1.3	Package depth	120 mm
DisplayPort version	1.1a	Package height	212 mm
Maximum resolution	3840 x 2160 pixels	Package weight	100 g
Supported graphics resolutions	1920 x 1200 (WUXGA), 3840 x 2160	<b>Logistics data</b>	
Bandwidth	297 MHz	Master (outer) case net weight	4 kg
Maximum refresh rate	60 Hz	Harmonized System (HS) code	84733080
Product colour	White	Master (outer) case width	270 mm
Jacket material	Plastic	Master (outer) case length	335 mm
<b>Operational conditions</b>		Master (outer) case height	230 mm
Operating temperature (T-T)	0 - 50 °C	Master (outer) case gross weight	4.58 kg
Storage temperature (T-T)	-20 - 60 °C	Products per master (outer) case	40 pc(s)
Operating relative humidity (H-H)	0 - 80%		



0672792006784



672792006784



4719264643736

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.