## Canon i-SENSYS MF752Cdw Laser A4 1200 x 1200 DPI 33 ppm Wi-Fi

Brand : Canon

Product family: i-SENSYS

Product code: 5455C017

Product name : MF752Cdw

- 3-in-1 colour office printer

- A4 print, copy, scan

- Wi-Fi, 5-inch display, Universal Print support, Application Library

33 ppm, A4, 1 Gb, LAN, USB, WiFi, LCD

Canon i-SENSYS MF752Cdw. Print technology: Laser, Printing: Colour printing, Maximum resolution: 1200 x 1200 DPI. Copying: Colour copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Duplex functions: Scan. Maximum ISO A-series paper size: A4. Wi-Fi. Direct printing. Product colour: White






Printing		Paper handling	
Print technology * Printing * Maximum resolution * Print speed (black, normal quality, A4/US Letter) * Warm-up time Time to first page (black, normal)	Laser Colour printing 1200 x 1200 DPI 33 ppm 14 s 7.1 s	Envelopes sizes Paper tray media weight	C5, Com-10, DL, Monarch 60 - 200 g/m²
		Ports & interfaces	
		Direct printing * USB port USB 2.0 ports quantity	✓ ✓ 1
Time to first page (colour, normal)	7.1 s	Network	
Copying Duplex copying * Copying *	✓ Colour copying	Wi-Fi * Ethernet LAN * Ethernet LAN data rates Wi-Fi standards	✓ ✓ 10 Mbit/s 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Maximum copy resolution * Maximum number of copies Copier resize ID-card copy function	600 x 600 DPI 999 copies 25 - 400%	Security algorithms Management protocols	64-bit WEP, 128-bit WEP, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPA2-TKIP SNMPv1, SNMPv3 (IPv4,IPv6)
Scanning		Performance	
Duplex scanning * Scanning * Optical scanning resolution * Scanner type * Scan to	Colour scanning 600 x 600 DPI ADF scanner Cloud, E-mail, FTP, USB	Internal memory * Built-in processor Processor frequency Sound power level (printing) Sound power level (standby)	1000 MB ✓ 1200 MHz 65 dB 41 dB
Input colour depth Output colour depth	24 bit 24 bit 256 ICA, TWAIN, WIA	Design	
Greyscale levels Scan drivers		Product colour * Market positioning *	White Business
Fax		Built-in display * Display	✓ LCD
Faxing *	×	Control type	Touch
Features		Colour display	✓
Recommended duty cycle Maximum duty cycle *	750 - 4000 pages per month 50000 pages per month	Power	
		Power consumption (max)	1380 W

Features		Power	
Duplex functions *	Scan	Power consumption (printing)	700 W
Printing colours *	Black, Cyan, Magenta, Yellow	Power consumption (standby)	24 W
	Cartridge 069 Black Cartridge 069H	Power consumption (sleep)	1 W
Replacement cartridges	Black Cartridge 069 Cyan Cartridge 069H Cyan Cartridge 069 Magenta Cartridge 069H Magenta Cartridge	Energy Star Typical Electricity Consumption (TEC)	0.3 kWh/week
	069 Yellow Cartridge 069H Yellow	AC input voltage	220 - 240 V
Input & output capacity	-	AC input frequency	50 - 60 Hz
Total number of input trays *	1	System requirements	
Total input capacity *	250 sheets	supported 8.1	Windows 10, Windows 11, Windows 8.1
Total output capacity *	150 sheets		Mac OS X 10.12 Sierra, Mac OS X
Multi-Purpose tray	✓		10.13 High Sierra, Mac OS X 10.14
Multi-Purpose tray input capacity	50 sheets		Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS
Auto document feeder (ADF)	4		X 10.2 Jaguar, Mac OS X 10.3
Auto document feeder (ADF) input capacity	50 sheets	Mac operating systems supported	Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6
Maximum input capacity	850 sheets		Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac
Paper handling			OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey
Maximum ISO A-series paper size *	A4	Linux operating systems supported	
Paper tray media types *	Coated paper, Heavy paper, Plain paper, Postcard, Recycled paper,	Linux operating systems supported	Vindows Server 2012, Windows
raper tray media types	Thin paper	Conver exercting systems supported	Server 2012 Core, Windows Server
ISO A-series sizes (A0A9) *	A4, A5, A6	Server operating systems supported	2012 R2, Windows Server 2016,
ISO B-series sizes (B0B9)	B5		Windows Server 2019
Non-ISO print media sizes	Executive, Letter, Statement	Operational conditions	
		Operating relative humidity (H-H)	20 - 80%
		Operating temperature (T-T)	10 - 30 °C
		Weight & dimensions	
		Width	425 mm
		Depth	461 mm
		Height	430 mm
		Weight	23.3 kg

 Packaging content

 Cartridge(s) included
 ✓

 Cables included
 AC



8714574670898

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.