## PHILIPS

## Philips 3000 series 27E1N3300A/00 LED display 68.6 cm (27") 1920 x 1080 pixels Full HD Black

Brand : Philips Product family: 3000 series Product code: 27E1N3300A/00

Product name: 27E1N3300A/00

Monitor 27E1N3300A USB-C monitor

Philips 3000 series 27E1N3300A/00 LED display 68.6 cm (27") 1920 x 1080 pixels Full HD Black:

This Philips USB-C multi-purpose monitor offers clutter-free setup. With a single cable you can view smooth high-resolution video, transfer data and charge your laptop. A true hub for mobile professionals. Philips 3000 series 27E1N3300A/00. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Display surface: Matt, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting. Product colour: Black









Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Tilt angle range	-5 - 20°
Display resolution *	1920 x 1080 pixels	On Screen Display (OSD)	✓
HD type *	Full HD		Simplified Chinese, Traditional
Native aspect ratio *	16:9		Chinese, Czech, German, Dutch, English, Spanish, Finnish, French,
Display technology *	LED	On Screen Display (OSD) languages	Greek, Hungarian, Italian, Japanese,
Panel type *	IPS		Korean, Polish, Portuguese, Russian
Backlight type	W-LED	Number of OCD languages	Swedish, Turkish, Ukrainian
Touchscreen *	×	Number of OSD languages	21
Display brightness (typical)	300 cd/m²	Plug and Play	• Constitution Clarett
Response time *	4 ms	LED indicators	Operation, Stand-by
Display surface	Matt	Power	
Anti-glare screen	✓	Energy efficiency class (SDR) *	Е
Screen shape *	Flat	Energy consumption (SDR) per 1000	) 26 kWh
Aspect ratio	16:9	hours *	20 KWII
Contrast ratio (typical) *	1000:1	Power consumption (typical) *	25.1 W
Dynamic contrast ratio marketing	Mega Infinity DCR	Power consumption (standby) *	0.5 W
name	,	Power consumption (off)	0.3 W
Maximum refresh rate *	75 Hz	AC input voltage	100 - 240 V
Viewing angle, horizontal	178°	AC input frequency	50 - 60 Hz
Viewing angle, vertical	178°	Power supply type	Internal
Display number of colours *	16.7 million colours	European Product Registry for	1073229
Response time (fast)	1 ms	Energy Labelling (EPREL) code	1073223
Pixel pitch	0.3114 x 0.3114 mm	Operational conditions	
Pixel density	81.59 ppi	Operating temperature (T-T)	0 - 40 °C
Horizontal scan range	30 - 85 kHz	Storage temperature (T-T)	-20 - 60 °C
Vertical scan range	48 - 75 Hz	Operating relative humidity (H-H)	20 - 80%
Viewable size, horizontal	59.8 cm	Operating altitude	0 - 3658 m
Viewable size, vertical	33.6 cm	Non-operating altitude	0 - 12192 m
Display diagonal (metric)	68.6 cm	. 3	·
DDC/CI	✓	Weight & dimensions	
Haze rate	25%	Width (with stand)	612 mm
Surface hardness	3H	Depth (with stand)	197 mm
sRGB coverage (typical)	122.8%	Height (with stand)	456 mm
NTSC coverage (typical)	106.2%	Weight (with stand)	6.06 kg

Display		Weight & dimensions	
Display sRGB	✓	Width (without stand)	612 mm
Performance		Depth (without stand)	55 mm
NVIDIA G-SYNC *	×	Height (without stand)	365 mm
AMD FreeSync *	7	Weight (without stand)	4.2 kg
Component video sync	Separate sync	Packaging data	
Flicker-free technology	✓	Package width	780 mm
Low Blue Light technology	✓	Package depth	186 mm
Multimedia		Package height	525 mm
Number of speakers	2	Package weight	10.1 kg
RMS rated power	3 W	Package type	Box
Built-in speaker(s) *	<b>√</b>	Packaging content	
Built-in camera *	×	Stand included	1
Design		Cables included	HDMI, USB Type-C to USB Type-C, AC
Market positioning *	Home	Manual	<b>√</b>
Product colour *	Black		•
Ports & interfaces		Sustainability	
Built-in USB hub *	1	Doesn't contain	Mercury, PVC/BFR
Dulic-III OOD Hub	•		
	3.2 Gen 1 (3.1 Gen 1)	Other features	
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Other features Compatible operating systems	Mac OS X, Windows 10 / 8.1 / 8 / 7
	3.2 Gen 1 (3.1 Gen 1)		Mac OS X, Windows 10 / 8.1 / 8 / 7 3.0
USB hub version USB Type-C DisplayPort Alternate	, ,	Compatible operating systems	
USB hub version USB Type-C DisplayPort Alternate Mode	<b>✓</b>	Compatible operating systems USB Power Delivery revision	3.0
USB hub version USB Type-C DisplayPort Alternate Mode USB Power Delivery	✓ ✓ 65 W	Compatible operating systems USB Power Delivery revision Exterior finish type	3.0 Textured
USB hub version USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity HDMI version	✓ ✓ 65 W ✓ 1 1.4	Compatible operating systems USB Power Delivery revision Exterior finish type Picture enhancement	3.0 Textured SmartImage game
USB hub version USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity	✓ ✓ 65 W ✓	Compatible operating systems USB Power Delivery revision Exterior finish type Picture enhancement Recyclable packaging material	3.0 Textured SmartImage game 100% CB; CE Mark; CU-EAC; EAEU RoHS; FCC Class B; ICES-003;
USB hub version USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity HDMI version	✓ ✓ 65 W ✓ 1 1.4	Compatible operating systems USB Power Delivery revision Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals	3.0 Textured SmartImage game 100% CB; CE Mark; CU-EAC; EAEU RoHS; FCC Class B; ICES-003; TUV/ISO9241-307; TUV-BAUART
USB hub version USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity HDMI version Audio output	✓ ✓ 65 W ✓ 1 1.4	Compatible operating systems USB Power Delivery revision Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Heavy metals free	3.0 Textured SmartImage game 100% CB; CE Mark; CU-EAC; EAEU RoHS; FCC Class B; ICES-003; TUV/ISO9241-307; TUV-BAUART Hg (mercury)
USB hub version USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity HDMI version Audio output  Ergonomics	✓ ✓ 65 W ✓ 1 1.4	Compatible operating systems USB Power Delivery revision Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Heavy metals free EasyRead mode	3.0 Textured SmartImage game 100% CB; CE Mark; CU-EAC; EAEU RoHS; FCC Class B; ICES-003; TUV/ISO9241-307; TUV-BAUART Hg (mercury)
USB hub version USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity HDMI version Audio output  Ergonomics VESA mounting *	65 W  1 1.4  100 x 100 mm	Compatible operating systems USB Power Delivery revision Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Heavy metals free EasyRead mode LowBlue mode Depth Compliance certificates	3.0 Textured SmartImage game 100% CB; CE Mark; CU-EAC; EAEU ROHS; FCC Class B; ICES-003; TUV/ISO9241-307; TUV-BAUART Hg (mercury)   55 mm ROHS
USB hub version USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity HDMI version Audio output  Ergonomics  VESA mounting * Panel mounting interface	65 W  1 1.4  100 x 100 mm	Compatible operating systems USB Power Delivery revision Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Heavy metals free EasyRead mode LowBlue mode Depth	3.0 Textured SmartImage game 100% CB; CE Mark; CU-EAC; EAEU RoHS; FCC Class B; ICES-003; TUV/ISO9241-307; TUV-BAUART Hg (mercury)
USB hub version USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity HDMI version Audio output  Ergonomics  VESA mounting * Panel mounting interface Cable lock slot *	65 W  1 1.4  100 x 100 mm	Compatible operating systems USB Power Delivery revision Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Heavy metals free EasyRead mode LowBlue mode Depth Compliance certificates	3.0 Textured SmartImage game 100% CB; CE Mark; CU-EAC; EAEU ROHS; FCC Class B; ICES-003; TUV/ISO9241-307; TUV-BAUART Hg (mercury)   55 mm ROHS
USB hub version USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity HDMI version Audio output  Ergonomics  VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type	✓ 65 W ✓ 1 1.4 ✓ 100 x 100 mm ✓ Kensington	Compatible operating systems USB Power Delivery revision Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Heavy metals free EasyRead mode LowBlue mode Depth Compliance certificates Mean time between failures (MTBF)	3.0 Textured SmartImage game 100% CB; CE Mark; CU-EAC; EAEU ROHS; FCC Class B; ICES-003; TUV/ISO9241-307; TUV-BAUART Hg (mercury)  55 mm ROHS 50000 h CB, CE Mark, CU-EAC, EAEU ROHS, FCC Class B, ICES-003,



8712581783365

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.