

AXIS W101 Body Worn Camera

Made with you in mind

AXIS W101 Body Worn Camera is a robust and easy-to-use body worn camera featuring the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. Axis Zipstream technology lowers bandwidth and storage requirements without compromising video quality. AXIS W101 offers over 12 hours of battery time at 1080p and charging with any USB-C[®] charger. Recording is activated automatically upon unholstering and person down. And the location of the camera can be continuously recorded with the built-in GNSS receiver (location tracking). Built-in Bluetooth[®], and network technologies provide wireless communication with, for example, the AXIS Body Worn Assistant mobile app.

- > [Always sharp video and clear audio](#)
- > [Operating time of up to 17 hours](#)
- > [KlickFast System](#)
- > [Location tracking](#)
- > [3-year warranty](#)



AXIS W101 Body Worn Camera

Camera		Casing
Image sensor	1/2.9" progressive scan RGB CMOS Sensitivity: 0.1 lux	IP67-rated Plastic casing Drop tested up to 2 m Color: Black NCS S 9000-N, White NCS S 1002-B
Lens	Focal length, 2.1 mm Horizontal field of view: 141° Vertical field of view: 82° Fixed iris, F2.1	Mounting Klick Fast System
Shutter speed	1/32000 s to 1/25 s with 50 Hz 1/32000 s to 1/30 s with 60 Hz	Sustainability PVC free
Video		Connectors Pogo pin pads, USB
Video compression	H.264 (MPEG-4 Part 10/AVC) High Profile	Operating conditions -20 °C to 55 °C (-4 °F to 131 °F) Humidity 10–100% RH (condensing)
Resolution	1920x1080, 1280x720	Storage conditions -20 °C to 45 °C (-4 °F to 113 °F) Humidity 5-95% RH (non-condensing)
Frame rate	25 fps at 50 Hz 30 fps at 60 Hz	Approvals EMC EN 55032 Class B, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), RCM AS/NZS CISPR 32 Class B Wireless EN 300328, EN 301489-1, EN 301489-17, EN 303413, FCC Part 15 Subpart C, RSS-247 Safety IEC/EN/UL 62368-1, EN 50360 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC/EN 60529 IP67 MIL-STD-810H (Method 501.7, 503.7, 505.7, 509.7, 512.6, 516.8)
Video streaming	Axis Zipstream for body worn	Dimensions Height: 94 mm (3.7 in) Width: 68 mm (1.7 in) Depth: 27 mm (1.1 in)
Audio		Weight 179 g (0.39 lb)
Audio encoding	AAC-LC One channel: 48 kHz, 128 kbps Two channels (optimized for post-processing mode): 48 kHz, 2x128 kbps	Included accessories AXIS TW1100 Clip Mount (only included in 1-pack)
Audio input/output	Built-in dual microphones	Optional accessories Klick Fast System for Body worn camera mounts, AXIS TW1200 Body Worn Mini Bullet Sensor, AXIS TW1201 Body Worn Mini Cube Sensor AXIS Body Worn Assistant app for Android, iOS For more accessories, see axis.com/bodyworn
Functionality	Voice enhancement	Warranty 3-year warranty, see axis.com/warranty . The 3-year warranty covers manufacturing defects in the product, including the battery.
General		
Battery	Li-ion, 3600 mAh, up to 17 hours operating time	
Storage	64 GB non-volatile memory, up to 30 hours of recorded video AES256 encryption standard	
Throughput	Camera to system controller: 100 Mbit/s	
Recording	Configurable audio and video pre-buffer 0, 15, 30, 60, and 90 s ^a	
Positioning system	GPS, GLONASS, Galileo	
Location	Start and end, track	
Sensor	6-axis gyro and accelerometer	
User interface	Status indicators, audio and vibration feedback	
Wireless interface	Bluetooth® Low Energy 4.1 IEEE 802.11b/g/n @ 2.4 GHz channels 1–11	
Cybersecurity	Signed firmware CJIS compliant encrypted internal storage (AES256) Axis Edge Vault with Axis device ID	

a. In complex scenes, when using maximum resolution and 90 s pre-buffer, the actual pre-buffer time may be slightly shorter than configured.

Environmental responsibility:
axis.com/environmental-responsibility