

AXIS W101 Body Worn Camera

Made with you in mind

AXIS W101 Body Worn Camera is a robust and easy-to-use body worn camera featuring the Klick Fast™ mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. Axis Zipstream technology lowers bandwidth and storage requirements without compromising video quality. AXIS W101 offers up to 17 hours of battery time and charging with any USB-C® charger. Recording is activated automatically upon unholstering and person down. And the location of the camera can be continuously recorded with the built-in GNSS receiver (location tracking). Built-in Bluetooth®, and network technologies provide wireless communication with, for example, the AXIS Body Worn Assistant mobile app.

- > [Always sharp video and clear audio](#)
- > [Operating time of up to 17 hours](#)
- > [Klick Fast™ System](#)
- > [Location tracking](#)
- > [3-year warranty](#)



AXIS W101 Body Worn Camera

Camera		Location	Track, start and end
Image sensor	1/2.9" progressive scan RGB CMOS Sensitivity: 0.1 lux	Sensor	6-axis gyroscope, accelerometer
Lens	Focal length, 2.1 mm Horizontal field of view: 141° Vertical field of view: 82° Fixed iris, F2.1	User interface	Status indicators, audio and vibration feedback
Shutter speed	1/32000 s to 1/25 s with 50 Hz 1/32000 s to 1/30 s with 60 Hz	Wireless interface	Bluetooth® Low Energy 4.1 IEEE 802.11b/g/n @ 2.4 GHz channels 1–11
Video		Casing	IP67-rated Plastic casing Drop tested up to 2 m
Video compression	H.264 (MPEG-4 Part 10/AVC) High Profile	Color	Black NCS S 9000-N White NCS S 1002-B
Resolution	1920x1080, 1280x720	Mounting	Klick Fast™ System
Frame rate	25 fps at 50 Hz 30 fps at 60 Hz	Sustainability	PVC free
Video streaming	Axis Zipstream for body worn	Connectors	Pogo pin pads USB
Audio		Operating conditions	-20 °C to 55 °C (-4 °F to 131 °F) Humidity 10–100% RH (condensing)
Audio encoding	AAC-LC One channel: 48 kHz, 128 kbps Two channels (optimized for post-processing mode): 48 kHz, 2x128 kbps	Storage conditions	-20 °C to 45 °C (-4 °F to 113 °F) Humidity 5-95% RH (non-condensing)
Audio input/output	Built-in dual microphones	Supply chain	TAA compliant
Functionality	Voice enhancement	Approvals	EMC EN 55032 Class B, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), RCM AS/NZS CISPR 32 Class B Wireless EN 300328, EN 301489-1, EN 301489-17, EN 303413, FCC Part 15 Subpart C, RSS-247 Safety IEC/EN/UL 62368-1, EN 50360, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC/EN 60529 IP67 MIL-STD-810H (Method 501.7, 503.7, 505.7, 509.7, 512.6, 516.8)
Cybersecurity		Dimensions	Height: 94 mm (3.7 in) Width: 68 mm (1.7 in) Depth: 27 mm (1.1 in)
Edge security	Software: Signed firmware, brute force delay protection, digest authentication, password protection, AES-XTS-Plain64 256bit encryption Hardware: Secure boot, Axis Edge Vault with Axis device ID, signed video, secure keystore (CC EAL4+ certified hardware protection of cryptographic operations and keys). CJIS compliant encrypted internal storage (AES256)	Weight	179 g (0.39 lb)
Network security	IEEE 802.1X (EAP-TLS), IEEE 802.1AR, HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, IP address filtering	Included accessories	AXIS TW1100 Clip Mount (only included in 1-pack)
Documentation	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity	Optional accessories	Klick Fast™ System for Body worn camera mounts, AXIS TW1200 Body Worn Mini Bullet Sensor, AXIS TW1201 Body Worn Mini Cube Sensor AXIS Body Worn Assistant app for Android, iOS For more accessories, see axis.com/bodyworn
General		Warranty	3-year warranty, see axis.com/warranty . The 3-year warranty covers manufacturing defects in the product, including the battery. Do not replace the 3.7 V ID1058 battery during the period under which the Axis Hardware Product is covered by the Axis 3-year Limited Hardware Warranty. Replacement of the battery carried out by any other party than Axis during the warranty period voids the main item's warranty. Contact Axis Support or your reseller for matters regarding the battery or other service-related matters.
Battery	Li-ion, 3600 mAh Up to 17 hours operating time in 720p Up to 15 hours operating time in 1080p	a. In complex scenes, when using maximum resolution and 90 s pre-buffer, the actual pre-buffer time may be slightly shorter than configured.	
Storage	64 GB non-volatile memory, up to 30 hours of recorded video AES256 encryption standard		
Throughput	Camera to system controller: 100 Mbit/s		
Recording	Configurable audio and video pre-buffer 0, 15, 30, 60, 90, and 120 s ^a		
Positioning system	GPS, GLONASS, Galileo		