



USB-C Male to USB A 3.2 Gen1 Female x2, RJ45 Female, HDMI 1.4 Female, VGA Female, USB-C Female 5 Gbps 4K UHD

V7UC-U3CRJ45HDVG-BLK

SKU: CA06363

Connect any USB-C Alt mode equipped PC or Mac to a USB 3.2 Gen 1 port, Ethernet, VGA or HDMI display or other devices with ease with the USB-C Adapter from V7. Lightweight and portable – the adapter can support resolutions up to 3840x2160 using HDMI or 1920x1200 using VGA. Adapter supports SST (Single Stream Transport) for single display setup only. The two USB 3.0 ports enables 5Gbps of transmission and charging; also downward compatible with USB 2.0 Type-C female port supports both data (5Gbps) and PD Charging 100W (20V/5A). Ethernet port supports 10/100/1000Mbps bandwidth. Comes with a 2 year warranty. All V7 adapters go through a rigorous testing process to ensure quality.

- Delivers a vivid, colorful picture up to 4K UHD (3820x2160) at 32bit Color and 30 Hz video signal
- Simple plug-and-play display connectivity for devices with USB-C Alt-Mode
- High grade shielding resistant to EMI and RF
- Built with corrosion-resistant connectors and strain relief for optimal signal transfer, fit and durability
- Versatile - choose between HDMI or VGA for display output
- Manufactured in our ISO certified facilities and backed by V7's warranty

General

SkU: CA06363
 Model: V7UC-U3CRJ45HDVG-BLK
 EAN: 0662919108828
 Warranty: 2 years
 Compliance: CE, FCC, RoHS, UKCA, WEEE
 Country Of Origin: Vietnam
 Package Type: Polybag

Color

Color: Black

Package Dimensions

Package Dimensions (L/W/H): 6.3 x 8.27 x 0 in (160 x 210 x 0.1 mm)
 Shipping Weight: 0.16 kg (0.35 lbs)

Product Dimensions

Product Weight: 0.15 kg (0.33 lbs)

Technical

Cable Jacket: PVC
 Maximum Resolution: 3840 X 2160
 Conductor: Nickel Plated
 USB Display Type: Alt-Mode
 Standard: HDMI 1.4, USB 3.2 Gen 1
 Connectors: HDMI, RJ45, USB, USB C, VGA
 Frequency: 30 Hz
 Hardware System Requirements: USB-C Port with Alt-Mode or Thunderbolt
 Connector 1: USB-C Male
 Connector 2: USB A Female x2, RJ45 Female, HDMI Female, VGA Female, USB-C Female
 Data Transfer Rate: USB 3.2 Gen1: 5Gbps, RJ45: 1Gbps



Specifications

SST Mode (Single Stream Transport)		
Ports	VGA	HDMI
1	1080P/60Hz	n/a
	n/a	4K/30Hz
2	1080P/60Hz	1080P/60Hz