

## APC Smart-UPS SMT1500RMI2UC - 4x C13, USB, Rack Mountable, 2U, SmartConnect, 1500VA

APC GITT

Brand : APC Product code: SMT1500RMI2UC

**Product name :** APC Smart-UPS SMT1500RMI2UC - 4x C13, USB, Rack Mountable, 2U, SmartConnect, 1500VA



APC Smart-UPS SMT1500RMI2UC - 4x C13, USB, Rack Mountable, 2U, SmartConnect, 1500VA APC Smart-UPS SMT1500RMI2UC - 4x C13, USB, Rack Mountable, 2U, SmartConnect, 1500VA. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 1000 W. AC outlet types: C13 coupler, IEC Jumpers, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 6 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 477 mm, Height: 86 mm

		P	
Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Output power capacity *	1.5 kVA	Rack capacity	2U
Output power *	1000 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	151 V	LED indicators	✓
Input operation voltage (max) *	302 V	Certification	CE, EAC, EN / IEC 62040-1, EN / IEC
Input frequency *	50/60 Hz	Certification	62040-2, Energy Star 1.0 (EU), RCM, TÜV, VDE
Output operation voltage (min)	220 V	On anational and distant	
Output operation voltage (max)	240 V	Operational conditions	
Output frequency	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	459 J	Storage temperature (T-T)	-15 - 45 °C
Response time	10 ms	Operating relative humidity (H-H)	0 - 95%
Noise level	46 dB	Storage relative humidity (H-H)	0 - 95%
Audible alarm(s)	<b>√</b>	Operating altitude	0 - 3000 m
Audible alarm modes	Alarm when on battery, Low battery alarm	Non-operating altitude	0 - 15000 m
Auto-restart	√	Technical details	
Ports & interfaces		Sustainability certificates	ENERGY STAR, Green Premium
AC outlet types	C13 coupler, IEC Jumpers	Weight & dimensions	
Power plug	C14 coupler	Width	432 mm
AC outlets quantity	4 AC outlet(s)	Depth	477 mm
USB port	<b>√</b>	Height	86 mm
Serial interface	1	Weight	26.1 kg
Serial interface type	RI-45	Package width	594 mm
SmartSlot	<i>'</i>	Package depth	603 mm
Battery		Package height	251 mm
•		Package weight	31.9 kg
Battery technology Number of batteries supported	Sealed Lead Acid (VRLA)  1	Packaging data	
Battery life (max)	6 year(s)	Rack mount kit	✓
Battery recharge time	3 h	Cables included	RS-232, USB cable
Hot-swap battery	<b>✓</b>	Manual	✓
Automatic battery test	1	Resource CD	✓
Cold start	<b>v</b>	Logistics data	
		Products per pallet	8 pc(s)
		Harmonized System (HS) code	85078000
		Other features	
		Output voltage	230 V
		Suspect voltage	230 .





731304333005

0731304333005

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.