

## Epson TM-M30II 203 x 203 DPI Wired & Wireless Direct thermal POS printer

**Brand :** Epson

**Product code:** C31CJ27111A0

**Product name :** TM-M30II

- Iconic design: Stylish, practical design with small footprint and clean lines
- Cost effective: Entry-level model (refreshed version of its predecessor, the TM-m30)
- Fast printing: Increased print speed of 250mm/s
- Direct printing from mobile devices: Without the need to install or update drivers
- Reliable: Epson's tried and trusted build quality

Compact mPOS receipt printer TM-M30II (111A0): USB + ETHERNET + BT, WHITE, PS, UK

Epson TM-M30II. Print technology: Direct thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 58 mm - 80 mm (Breite), Maximum printing width: 8 cm. Connectivity technology: Wired & Wireless, USB connector: USB Type-A / USB Type-B. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 1.5 million cuts. Product colour: White



| Printing                          |                         | Operational conditions            |  |
|-----------------------------------|-------------------------|-----------------------------------|--|
| Maximum resolution                | 203 x 203 DPI           | Storage temperature (T-T)         | -20 - 60 °C  |
| Print speed                       | 250 mm/sec              | Operating relative humidity (H-H) | 10 - 90%   |
| Print speed (receipt)             | 250 mm/sec              | Storage relative humidity (H-H)   | 10 - 90%   |
| Printing characters               | Text, Graphic, Barcode  | System requirements               |  |
| Character sets                    | ANK                     | Pre-installed software            | TMNet WebConfig, ePOS-Device, ePOS-Display, ePOS-Print |
| Print technology *                | Direct thermal          | Weight & dimensions               |  |
| Type *                            | POS printer             | Width                             | 127 mm   |
| Paper handling                    |                         | Depth                             | 127 mm   |
| Maximum roll diameter             | 8.3 cm                  | Height                            | 127 mm   |
| Supported paper width             | 58 mm - 80 mm (Breite)  | Weight                            | 1.3 kg   |
| Maximum printing width            | 8 cm                    | Packaging data                    |  |
| Ports & interfaces                |                         | Quantity per pack                 | 1 pc(s)  |
| USB port *                        | ✓                       | Package width                     | 193 mm   |
| USB 2.0 ports quantity            | 2                       | Package depth                     | 235 mm   |
| USB connector                     | USB Type-A / USB Type-B | Package height                    | 233 mm   |
| Bluetooth                         | ✓                       | Package weight                    | 2.2 kg   |
| Connectivity technology *         | Wired & Wireless        | Packaging content                 |  |
| Near Field Communication (NFC)    | ✓                       | AC adapter included               | ✓  |
| Network                           |                         | Print technology                  |  |
| Ethernet LAN *                    | ✓                       | Column capacity                   | 48/57  |
| Wi-Fi *                           | ✗                       | Logistics data                    |  |
| Features                          |                         | Pallet weight (UK)                | 0 g  |
| Sound pressure level (printing)   | 55 dB                   | Harmonized System (HS) code       | 84433210   |
| Mean time between failures (MTBF) | 360000 h                | Products per master (outer) case  | 4 pc(s)  |
| Half-cutter                       | ✓                       | Master (outer) case width         | 400 mm   |
| Autocutter durability             | 1.5 million cuts        | Master (outer) case length        | 490 mm   |
| Print head life                   | 150 km                  | Master (outer) case height        | 255 mm   |
| Country of origin                 | Philippines             | Master (outer) case gross weight  | 0 g  |
| Mounting position                 | Horizontal/Vertical     | Products per pallet               | 128 pc(s)  |
| Wall mountable                    | ✓                       |                                   |  |

| Features                    |  | Logistics data                      |                     |
|-----------------------------|--|-------------------------------------|---------------------|
| Built-in sensors details    | Paper End Sensor, Paper Near End Sensor, Papier-Sensor | Pallet gross weight                 | 0 g                 |
|                             |  | Products per pallet (UK)            | 192 pc(s)           |
| Design                      |  | Technical details                   |                     |
| Product colour *            | White  | Font styles                         | ANK                 |
|                             |  | Lifetime                            | 17000000 lines      |
| Power                       |  | Other features                      |                     |
| Power source type *         | AC   | Buffer size                         | 12 KB               |
| Power plug type             | Type G   | Mean cycles between failures (MCBF) | 65000000            |
| Operational conditions      |  | Print head life                     | 150.000.000 Impulse |
| Operating temperature (T-T) | 5 - 45 °C  |                                     |                     |



8715946688527

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-NOV-2024. Prints or copies of Information are only valid on the printed Publication date