![DELL]

DELL C Series 27 Video Conferencing Monitor - C2722DE

Brand : DELL   **Product family:** C Series   **Product code:** DELL-C2722DE

Product name : Dell 27 Video
Conferencing Monitor - C2722DE

- 68.6cm (27") Quad HD 2560 x 1440 LED IPS
- 8ms, 16:9, 350cd/m², 1000:1
- USB, HDMI, DisplayPort
68.6cm (27") Quad HD 2560 x 1440 LED IPS, 16:9, 350cd/m², 16.78M, 8ms, 1000:1

DELL C Series 27 Video Conferencing Monitor - C2722DE:

Collaborate like you're there on a 27-inch QHD monitor with an integrated 5MP camera, dual 5W speakers and a dedicated Microsoft Teams button.
DELL C Series 27 Video Conferencing Monitor - C2722DE. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black

Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Panel mounting interface	100 x 100 mm
Display resolution *	2560 x 1440 pixels	Cable lock slot *	✔
HD type *	Quad HD	Height adjustment *	✔
Native aspect ratio *	16:9	Height adjustment	12 cm
Display technology *	LCD	Pivot	✔
Panel type *	IPS	Pivot angle	-90 - 90°
Backlight type	LED	Swivelling	✔
Touchscreen *	✘	Swivel angle range	-45 - 45°
Display brightness (typical)	350 cd/m²	Tilt adjustment	✔
Response time *	8 ms	Tilt angle range	-5 - 21°
Anti-glare screen	✔	On Screen Display (OSD)	✔
Screen shape *	Flat	LED indicators	✔
Supported graphics resolutions	2560 x 1440	**Power**	
Supported video modes	480i, 480p, 576i, 720p, 1080i, 1080p	Energy efficiency class (SDR) *	F
Contrast ratio (typical) *	1000:1	Energy efficiency class (HDR) *	Not available
Maximum refresh rate *	60 Hz	Energy consumption (SDR) per 1000 hours *	23 kWh
Viewing angle, horizontal	178°	Power consumption (typical) *	22.8 W
Viewing angle, vertical	178°	Power consumption (standby) *	0.3 W
Display number of colours *	16.78 million colours	Power consumption (max)	210 W
Response time (fast)	6 ms	Power consumption (off)	0.2 W
Pixel pitch	0.2331 x 0.2331 mm	AC input voltage	100 - 240 V
Pixel density	108.79 ppi	AC input frequency	50 - 60 Hz
Horizontal scan range	30 - 90 kHz	Power supply type	Internal
Vertical scan range	56 - 76 Hz	Energy efficiency scale	A to G
Viewable size, horizontal	59.7 cm	European Product Registry for Energy Labelling (EPREL) code	394149
Viewable size, vertical	33.6 cm	**Operational conditions**	
Display diagonal (metric)	68.47 cm		
High Dynamic Range (HDR) supported	✘	Operating temperature (T-T)	0 - 40 °C

Display

sRGB coverage (typical)	99%

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘
Flicker-free technology	✔
Low Blue Light technology	✔

Multimedia

Number of speakers	2
RMS rated power	10 W
Built-in speaker(s) *	✔
Megapixel (approx.)	5 MP
Built-in microphone	✔
Built-in camera *	✔

Design

Market positioning *	Home
Product colour *	Black
Front bezel colour	Black
Detachable stand	✔
Feet colour	Silver

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	3
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	✔
USB Power Delivery up to	90 W
DVI port	✘
HDMI *	✔
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.2
Audio input	✘
Headphone out *	✘
Headphone outputs	1
Headphone connectivity	3.5 mm
HDCP	✔
AC (power) in	✔

Network

Wi-Fi	✘

Ergonomics

VESA mounting *	✔

Operational conditions

Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m
Non-operating altitude	5000 - 12192 m

Weight & dimensions

Width (with stand)	612.3 mm
Depth (with stand)	230 mm
Height (with stand)	565.6 mm
Weight (with stand)	8.8 kg
Width (without stand)	612.3 mm
Depth (without stand)	53.9 mm
Height (without stand)	425.4 mm
Weight (without stand)	5.74 kg
Bezel width (side)	7.8 mm
Bezel width (top)	7.8 mm
Bezel width (bottom)	5.2 cm

Packaging data

Package weight	12.6 kg
USB cable length	1.8 m

Packaging content

Stand included	✔
Cables included	AC, DisplayPort, USB Type-A to USB Type-B, USB Type-C to USB Type-C
Quick start guide	✔
DisplayPort cable length	1.8 m

Sustainability

Sustainability certificates	ENERGY STAR
Doesn't contain	PVC/BFR

Carbon footprint

Total carbon footprint (kg of CO2e)	642
Total carbon emissions, standard deviation (kg of CO2e)	108
Carbon emissions, manufacturing (kg of CO2e)	402
Carbon emissions, logistics (kg of CO2e)	68
Carbon emissions, energy usage (kg of CO2e)	169
Carbon emissions, end-of-life (kg of CO2e)	4
Total carbon emissions, w/o use phase (kg of CO2e)	473

Other features

Heavy metals free	Hg (mercury)
Compliance certificates	RoHS
Ethernet LAN (RJ-45) ports	1

Logistics data

Harmonized System (HS) code	85285210

5397184504918

5704174819103

5715063102374