



AOC G2 U28G2XU/BK computer monitor 71.1 cm (28") 3840 x 2160 pixels 4K Ultra HD LED Black, Red

Brand : AOC

Product family: G2

Product code: U28G2XU/BK

Product name : U28G2XU/BK

U28G2XU/BK28" monitor with 4K UHD and 144 Hz, perfect for RTS and RPG gaming

[AOC G2 U28G2XU/BK computer monitor 71.1 cm \(28"\) 3840 x 2160 pixels 4K Ultra HD LED Black, Red:](#)

28" monitor with 4K UHD and 144 Hz, perfect for RTS and RPG gaming

The most beautiful and clear images to accompany your adventures through the virtual realm: The new AOC U28G2XU comes with a stunning 4K UHD resolution while still sporting a 144Hz response rate for a smooth experience. With HDR400 and 1ms response time, this IPS-monitor is the perfect choice for those who enjoy the vivid worlds of RTS and RPG titles.

AOC G2 U28G2XU/BK. Display diagonal: 71.1 cm (28"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 1 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black, Red



Display		Ergonomics	
Display diagonal *	71.1 cm (28")	Panel mounting interface	100 x 100 mm
Display resolution *	3840 x 2160 pixels	Cable lock slot *	✓
HD type *	4K Ultra HD	Cable lock slot type	Kensington
Native aspect ratio *	16:9	Height adjustment *	✓
Display technology *	LED	Height adjustment	13 cm
Panel type *	IPS	Pivot	✓
Backlight type	W-LED	Swivelling	✓
Touchscreen *	✗	Swivel angle range	-32 - 32°
Display brightness (typical)	370 cd/m ²	Tilt angle range	-5 - 21.5°
Response time *	1 ms	On Screen Display (OSD)	✓
Anti-glare screen	✓	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Croatian, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Screen shape *	Flat		
Contrast ratio (typical) *	1000:1		
Contrast ratio (dynamic)	80000000:1		
Maximum refresh rate *	144 Hz		
Viewing angle, horizontal	178°		
Viewing angle, vertical	178°		
Display number of colours *	16.7 million colours		
Vertical scan range	48 - 144 Hz		
Display diagonal (metric)	71.1 cm		
High Dynamic Range (HDR) supported	✓		
High Dynamic Range (HDR) technology	DisplayHDR 400		
Surface hardness	3H		
Colour depth	8 bit		
Adobe RGB coverage	105%		
Performance		Power	
NVIDIA G-SYNC *	✗	Energy efficiency class (SDR) *	G
		Energy efficiency class (HDR) *	G
		Energy consumption (SDR) per 1000 hours *	33 kWh
		Energy consumption (HDR) per 1000 hours *	60 kWh
		Power consumption (standby) *	0.3 W
		Power consumption (off)	0.5 W
		AC input voltage	100 - 240 V
		AC input frequency	50 - 60 Hz
		Energy efficiency scale	A to G
		European Product Registry for Energy Labelling (EPREL) code	553593
		External power adapter	✗

Performance		Weight & dimensions	
AMD FreeSync *	✓	Width (with stand)	636.4 mm
AMD FreeSync type	FreeSync Premium	Depth (with stand)	244.9 mm
AMD FreeSync refresh rate range	48 - 144 Hz	Height (with stand)	469.5 mm
Fast charging	✓	Weight (with stand)	6.13 kg
Low Blue Light technology	✓	Width (without stand)	636.4 mm
Multimedia		Depth (without stand)	49.3 mm
Number of speakers	2	Height (without stand)	368.5 mm
RMS rated power	3 W	Packaging data	
Built-in speaker(s) *	✓	Package width	160 mm
Built-in microphone	✗	Package depth	593 mm
Built-in camera *	✗	Package height	715 mm
Design		Package weight	8.62 kg
Market positioning *	Gaming	Package type	Box
Product colour *	Black, Red	Packaging content	
Front bezel colour	Black/Red	Cables included	DisplayPort, HDMI
Detachable stand	✓	DisplayPort cable length	1.8 m
Ports & interfaces		HDMI cable length	1.8 m
Built-in USB hub *	✓	Sustainability	
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Sustainability compliance	✓
USB Type-A downstream ports quantity	4	Other features	
HDMI *	✓	Country of origin	China
HDMI ports quantity	2	Exterior finish type	Textured
HDMI version	2.0	Recyclable packaging material	100%
DisplayPorts quantity	2	Heavy metals free	Hg (mercury)
DisplayPort version	1.4	Compliance certificates	CE, REACH, RoHS
Headphone out *	✓	Light effects	✗
Headphone connectivity	3.5 mm	Certification	True
AC (power) in	✓	Logistics data	
Ergonomics		Commodity Classification	
VESA mounting *	✓	Automated Tracking System (CCATS)	8528521000
		Harmonized System (HS) code	85285210



4038986189927

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-NOV-2024. Prints or copies of Information are only valid on the printed Publication date