



DELL P Series P2422HE LED display 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black

Brand : DELL

Product family: P Series

Product code: P2422HE

Product name : P2422HE

DELL P Series P2422HE. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	Swivelling	✓
Display resolution *	1920 x 1080 pixels	Swivel angle range	-45 - 45°
HD type *	Full HD	Tilt adjustment	✓
Native aspect ratio *	16:9	Tilt angle range	-5 - 21°
Display technology *	LCD	On Screen Display (OSD)	✓
Panel type *	IPS	Plug and Play	✓
Backlight type	LED	LED indicators	Power
Touchscreen *	✗	Power	
Display brightness (typical)	250 cd/m ²	Energy efficiency class (SDR) *	D
Response time *	8 ms	Energy consumption (SDR) per 1000 hours *	15 kWh
Anti-glare screen	✓	Power consumption (standby) *	0.3 W
Screen shape *	Flat	Power consumption (max)	48 W
Supported graphics resolutions	1920 x 1080 (HD 1080)	Power consumption (off)	0.2 W
Supported video modes	480p, 576p, 720p, 1080i, 1080p	AC input voltage	100 - 240 V
Aspect ratio	16:9	AC input frequency	50 - 60 Hz
Contrast ratio (typical) *	1000:1	Energy efficiency scale	A to G
Maximum refresh rate *	60 Hz	European Product Registry for Energy Labelling (EPREL) code	549713
Viewing angle, horizontal	178°	Operational conditions	
Viewing angle, vertical	178°	Operating temperature (T-T)	0 - 40 °C
Display number of colours *	16.7 million colours	Storage temperature (T-T)	-20 - 60 °C
Response time (fast)	5 ms	Operating relative humidity (H-H)	10 - 80%
Pixel pitch	0.2745 x 0.2745 mm	Storage relative humidity (H-H)	5 - 90%
Pixel density	93 ppi	Operating altitude	0 - 5000 m
Horizontal scan range	30 - 83 kHz	Non-operating altitude	0 - 12192 m
Vertical scan range	50 - 76 Hz	Weight & dimensions	
Viewable size, horizontal	52.7 cm	Width (with stand)	537.8 mm
Viewable size, vertical	29.6 cm		
Viewable size diagonal	60.5 cm		
Display diagonal (metric)	60.47 cm		

Display		Weight & dimensions	
Colour depth	6 bit	Depth (with stand)	179.6 mm
sRGB coverage (typical)	99%	Height (with stand)	496.1 mm
Performance		Weight (with stand)	5.15 kg
Flicker-free technology	✓	Width (without stand)	537.8 mm
Low Blue Light technology	✓	Depth (without stand)	52.1 mm
Multimedia		Height (without stand)	318.5 mm
Built-in speaker(s) *	✗	Weight (without stand)	3.39 kg
Built-in camera *	✗	Bezel width (side)	5.38 mm
Design		Bezel width (top)	5.38 mm
Market positioning *	Home	Bezel width (bottom)	1.67 cm
Product colour *	Black	Packaging content	
Front bezel colour	Black	Stand included	✓
Detachable stand	✓	Cables included	AC, DisplayPort, USB Type-C
Feet colour	Silver	Quick start guide	✓
Ports & interfaces		Sustainability	
Built-in USB hub *	✓	Sustainability certificates	ENERGY STAR, EPEAT Gold
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)	Doesn't contain	PVC/BFR
USB upstream port type	USB Type-B	Carbon footprint	
Number of upstream ports	1	Total carbon footprint (kg of CO2e)	542
USB Type-A downstream ports quantity	4	Total carbon emissions, standard deviation (kg of CO2e)	96
USB Type-C DisplayPort Alternate Mode	✓	Carbon emissions, manufacturing (kg of CO2e)	347
USB Power Delivery up to	65 W	Carbon emissions, logistics (kg of CO2e)	42
HDMI *	✓	Carbon emissions, energy usage (kg of CO2e)	151
HDMI ports quantity	1	Carbon emissions, end-of-life (kg of CO2e)	2
HDMI version	1.4	Total carbon emissions, w/o use phase (kg of CO2e)	391
DisplayPorts quantity	2	PAIA version	1.2.15, 2021
DisplayPort version	1.2	Other features	
Headphone out *	✗	Heavy metals free	Hg (mercury)
HDCP	✓	Compliance certificates	RoHS
AC (power) in	✓	Logistics data	
Ergonomics		Harmonized System (HS) code	85285210
VESA mounting *	✓		
Panel mounting interface	100 x 100 mm		
Cable lock slot *	✓		
Height adjustment *	✓		
Height adjustment	15 cm		
Pivot angle	-90 - 90°		



0884116398066



884116398066

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-NOV-2024. Prints or copies of Information are only valid on the printed Publication date