

DELL P Series 24 Monitor - P2423

Brand : DELL

Product family: P Series

Product code: DELL-P2423

Product name : Dell 24 Monitor - P2423

- 61.0cm (24") WUXGA 1920 x 1200 LED IPS
- 5ms, 16:10, 300cd/m², 1000:1
- USB, VGA, DVI, HDMI, DisplayPort
61.0cm (24") WUXGA 1920 x 1200 LED IPS, 16:10, 300cd/m², 16.7M, 5ms, 178°/178°, 1000:1

DELL P Series 24 Monitor - P2423:

See everything on our 24-inch WUXGA 16:10 monitor with versatile connectivity, a three-sided ultrathin bezel and ComfortView Plus.

DELL P Series 24 Monitor - P2423. Display diagonal: 61 cm (24"), Display resolution: 1920 x 1200 pixels, HD type: WUXGA, Display technology: LCD, Response time: 5 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black









Display		Ergonomics	
Display diagonal *61 cm (24")Display resolution *1920 x 1200 pixelsHD type *WUXGANative aspect ratio *16:10Display technology *LCDPanel type *IPSBacklight typeLEDTouchscreen *XDisplay brightness (typical)300 cd/m²Response time *5 msAnti-glare screen✓Screen shape *FlatSupported video modes480p, 576p, 720p, 1080i, 1080pContrast ratio (typical) *1000:1Maximum refresh rate *60 HzViewing angle, horizontal178°Display number of colours *16.7 million coloursResponse time (fast)8 msPixel pitch0.27 x 0.27 mm	Tilt adjustment Tilt angle range On Screen Display (OSD) Plug and Play LED indicators	✓ -5 - 21° ✓	
	Power Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Input current Power supply type Energy efficiency scale European Product Registry for	14.8 W 0.3 W 48 W 0.2 W 100 - 240 V 50 - 60 Hz 1.5 A Internal A to G	
Pixel density Horizontal scan range Vertical scan range Viewable size, horizontal Viewable size, vertical Viewable size diagonal Display diagonal (metric) High Dynamic Range (HDR) supported	94 ppi 30 - 83 kHz 56 - 76 Hz 51.8 cm 32.4 cm 61 cm 60.96 cm	European House (tegisti) for Energy Labelling (EPREL) code Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	1043228 0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m

Display		Weight & dimensions	
Colour gamut standard	sRGB	Width (with stand)	531 mm
Colour gamut	99%	Depth (with stand)	179.6 mm
Performance		Height (with stand)	510.8 mm
NVIDIA G-SYNC *	×	Weight (with stand)	5.23 kg
AMD FreeSync *	x	Width (without stand)	531 mm
Low Blue Light technology	7	Depth (without stand)	53.3 mm
Multimedia		Height (without stand)	348.1 mm
		Weight (without stand)	3.52 kg
Built-in speaker(s) *	X	Bezel width (side)	6.3 mm
Built-in camera *	×	Bezel width (top) Bezel width (bottom)	6.3 mm 1.78 cm
Design			1.78 Cm
Market positioning *	Business	Packaging data	
Product colour *	Black	Package weight	7.71 kg
Front bezel colour	Black	Packaging content	
Detachable stand	√ Ciluer	Stand included	1
Feet colour	Silver	Cables included	AC, DisplayPort, USB, VGA
Ports & interfaces		Quick start guide	✓
Built-in USB hub *	1	Sustainability	
USB upstream port type	USB Type-B	Sustainability certificates	ENERGY STAR, TCO
Number of USB Type-B upstream ports quantity	1	Doesn't contain	PVC/BFR
USB Type-A downstream ports	4	Carbon footprint	
quantity	4	Total carbon footprint (kg of CO2e)	565
VGA (D-Sub) ports quantity	1	Total carbon emissions, standard	
DVI port	V	deviation (kg of CO2e)	122
DVI-I ports quantity HDMI *	1	Carbon emissions, manufacturing	354
HDMI ports quantity	1	(kg of CO2e) Carbon emissions, logistics (kg of	
HDMI version	1.4	CO2e)	68
DisplayPorts quantity	1	Carbon emissions, energy usage (kg	138
DisplayPort version	1.2	of CO2e)	
Headphone out *	x	Carbon emissions, end-of-life (kg of CO2e)	4
AC (power) in	<	Total carbon emissions, w/o use	426
Network		phase (kg of CO2e)	
Wi-Fi	×	PAIA version	1.3.0
Ergonomics		Other features	
VESA mounting *	1	Heavy metals free	Hg (mercury)
Panel mounting interface	100 x 100 mm	Compliance certificates	RoHS
Cable lock slot *	✓	Logistics data	
Height adjustment *	1	Harmonized System (HS) code	85285210
Height adjustment	15 cm		
Pivot	✓		
Pivot angle	90 - 90°		
Swivelling	1		
Swivel angle range	-45 - 45°		














Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.