

Quantum®

SuperLoader 3



> DATASHEET

Advanced Automation at an Affordable Price: Now with DATASTOR Shield Deduplication Software

Designed for simple and reliable backups, the SuperLoader® 3 offers an exclusive package of advanced features including StorageCare® Guardian, remote management, and barcode reader—all at no additional cost. It also gives you the widest range of drive options in the industry to support data requirements up to 1,920TB—with the flexibility to expand as your storage needs grow.

Quantum SuperLoader 3 LTO-7, LTO-6, and LTO-5 models now include DATASTOR Shield™ backup software with deduplication to supercharge your backup. Quantum and DATASTOR have teamed up to provide the first backup with deduplication straight to tape. This technology, which reduces backups significantly (up to 20X), allows you to store more data per tape than competitive models.

The SuperLoader 3 brings you a full suite of advanced features at an affordable price with easy integration, an intuitive user interface, and compatibility with a broad range of backup software packages. And because you can easily expand from 8 to 16 cartridge slots, your investment is protected as your needs grow.

Customers may also choose additional service level uplifts to 5×9×ND and 7×24×4 for maximum availability and faster response times.

FEATURES & BENEFITS

- Complete Solution with StorageCare Guardian – A remote monitoring and diagnostics tool that proactively monitors your SuperLoader 3 over the Internet and uses intelligent diagnostics to remotely service the unit if necessary
- Compatible with all major backup software packages, environments, and infrastructures
- Backup with Deduplication – Includes DATASTOR Shield backup software; reduces data by 20X
- The only autoloader that supports 16 cartridges in a 2U rackmount unit
- Access from any web-based browser for remote diagnostics, operations, software upgrades and maintenance
- Removable magazine(s) provide fast, easy cartridge access
- Up to 240TB* of capacity with standard compression; up to 1,920TB of capacity with DATASTOR Shield
- Up to 2.7TB/hr* transfer rate
- Scalable from 8 to 16 cartridge slots
- 2U rackmountable form factor
- State-of-the-art performance and energy efficiency
- Available with SAS interfaces (LTO-7, LTO-6, and LTO-5), and with SCSI and SAS interfaces (all other LTO)

*Reduce Data by 20X
with Included Backup Software!*

*2.5:1 compression LTO-7 and LTO-6, 2:1 other LTO, 20:1 deduplication



> LEARN MORE:
www.quantum.com/superloader3

TECHNICAL SPECIFICATIONS

DRIVE CAPACITY AND PERFORMANCE

Drive Type	Autoloader Capacity Native/Compressed/ Deduplicated* (TB)	Performance Native/Compressed/ Deduplicated* (TB/hr)
LTO-7HH	96 / 240 / 1,920	1.08 / 2.70 / 21.60
LTO-6HH	40 / 100 / 800	0.576 / 1.44 / 11.52
LTO-5HH	24 / 48 / 480	0.504 / 1.0 / 10.0
LTO-4HH	12.8 / 25.6 / 256	0.288 / 0.576 / 5.76

*2.5:1 compression LTO-7 and LTO-6, 2:1 other LTO, 20:1 deduplication

HOST INTERFACE

LTO-7HH:	6Gb/s SAS
LTO-6HH:	6Gb/s SAS
LTO-5HH:	6Gb/s SAS
LTO-4HH:	3Gb/s SAS, Ultra 320 SCSI

BACKUP SOFTWARE

Included Software:	DATASTOR Shield Single Server Backup
Deduplication Rate:	20:1 (typical)
Software Compatibility:	Windows Only
Backup Methods:	Disk-to-disk-to-tape, disk-to-tape, archive-to-tape in native format
Upgradeable:	Yes to multiple servers, SQL, Exchange, SharePoint, Bare Metal, Cloud and other functionality

RELIABILITY

MSBF:	1,500,000
MTTR:	<30 min
Cartridge Capacity:	8 or 16 cartridges
Management Requirements:	Integrated Web-based Management standard on all SuperLoader 3 products
Power Requirements:	90 to 256VAC

PHYSICAL SPECIFICATIONS

Width (in/cm)	16.7 / 42.42
Height (in/cm)	3.41 / 8.66
Length (in/cm)	27.5 / 69.85
Weight (lbs/kg)	31 / 14.06

WARRANTY

1 Year Rapid Exchange

OPERATIONS

Cartridge Loader:	Single front loader slot (import port) and bulk cartridge loading in removable active magazines.
On-board Remote Management Tools:	10/100baseT Ethernet
Available Operations:	Review System Status, Remote Diagnostics, Browse System Logs, Configuration, Firmware Upgrades, Drive Operations, Remote Management, Check Inventory, System Upgrades Standard
Barcode Reader:	

ENVIRONMENTAL

Temperature Range (Dry Bulb):	Operating +10°C to +35°C Non-Operating -40°C to +65°C
Temperature Variation:	Operating 10°C per hour Non-Operating 20°C per hour
Humidity:	Operating 20% to 80% non-condensing Non-Operating 10% to 90% non-condensing Gradient 10% per hour without condensation Operating 26°C max Non-Operating 29°C max
Web Bulb:	Operating -500 to 10,000 feet (-153m to 3048m) Non-Operating -500 to 40,000 feet (-153m to 12192m)
Altitude:	

AGENCY APPROVALS

Safety:	U.S. (UL 1950) Canada (CSA 22.2 No. 950) Europe (EN60950/IEC 950) EMI/RFI ECC Directive 89336 CD BS6527 (UK) EN 55022 (EU) EN 55024 (EU) CFR 47, 1995 FCC Rules Part 15B Class B (MDOC) IEC-003 Canada V-3/97.04 VCCI Class B (Japan) AS/NZS 3548 Australia/New Zealand (C-tick Mark) CNS 13438 BSMI Class A Taiwan CD, VCCI, UL, FCC, CSA
Agency Markings:	

COMPATIBILITY

Software/Hardware:	Go to www.quantum.com for the most up-to-date tested solutions.
--------------------	--

Model Numbers and Descriptions

EC-LLFAE-YF-C LTO-4HH SAS, 8 Slots/1 Magazine	EC-LLPAE-YF-C LTO-5HH SAS, 8 Slots/1 Magazine	E7-L2PAE-HF-C LTO-5HH SAS, HBA (6Gb/s, PCIe), 10 pcs Media, 16 Slot/2 Magazine
EC-L2FAE-YF-C LTO-4HH SAS, 16 Slots/2 Magazine	EC-L2PAE-YF-C LTO-5HH SAS, 16 Slots/2 Magazines	E7-L2SAE-HF-C LTO-6HH SAS, HBA (6Gb/s, PCIe), 10 pcs Media, 16 Slot/2 Magazine
EC-LLKAA-YF-B LTO-4HH SCSI, 8 Slots/1 Magazine	E7-LLSAE-YF-C LTO-6HH SAS, 8 Slot/1 Magazine	E7-L2YAE-HF LTO-7HH SAS, HBA (6Gb/s, PCIe), 10 pcs Media, 16 Slot/2 Magazine
EC-L2KAA-YF-B LTO-4HH SCSI, 16 Slots/2 Magazines	E7-L2SAE-YF-C LTO-6HH SAS, 16 Slot/2 Magazine	
	E7-LLYAE-YF LTO-7HH SAS, 8 Slot/1 Magazine	
	E7-L2YAE-YF LTO-7HH SAS, 16 Slot/2 Magazine	

*European models with LTO have -YE instead of -YF, or -HE instead of -HF

To learn more about Quantum SuperLoader 3, please visit www.quantum.com/superloader3

©2016 Quantum Corporation (NYSE:QTM). All rights reserved. Quantum, the Quantum logo, StorageCare and SuperLoader are registered trademarks of Quantum Corporation and its affiliates in the United States and/or other countries. Linear Tape-Open, LTO, the LTO Logo, Ultrium and the Ultrium Logo are registered trademarks of Hewlett Packard Enterprise, IBM and Quantum in the USA and other countries. All other trademarks are the property of their respective owners.

Quantum®

www.quantum.com • 800-677-6268

DS00379A-v14 Mar 2016