

Lindy 1.5m USB 3.2 Type A to C Cable, 10Gbps, 5A, PD, Anthra Line

Brand : Lindy Product code: 36912

Product name: 1.5m USB 3.2 Type A to C Cable, 10Gbps,


5A, PD, Anthra Line

- Professional choice USB 3.2 Gen 2 Type A to C, 5A (100W), cable for commercial and high performance AV and IT installations
- SuperSpeed USB 10Gbps supports data transfer speeds up to 10Gbps (USB 3.1, USB 3.1 Gen 2)
- Robust PVC housing, 24K gold plated connectors and contacts
- Triple shielded cable, corrosion resistant tinned copper conductors
- 2 year warranty

1.5m USB 3.2 Type A to C Cable, 10Gbps, 5A, PD, Anthra Line Lindy 1.5m USB 3.2 Type A to C Cable, 10Gbps, 5A, PD, Anthra Line. Cable length: 1.5 m. Connector 1: USB C, Connector 2: USB A, USB version: USB 3.2 Gen 2 (3.1 Gen 2), Maximum data transfer rate: 10 Gbit/s, Connector contacts plating: Gold, Product colour: Black, Grey, Magnetically shielded



Features		Features	
USB version * Connector 1 * Connector 2 * Connector 1 gender *	or 1 * USB C or 2 * USB A or 1 gender * Male or 2 gender * Male or 1 form factor Straight or 2 form factor Straight or 2 form factor Gold or material Gold material Phosphor bronze or contacts plating Gold cally shielded cket material Polyvinyl chloride (PVC) or material Tinned copper or shielding Or shield material Copper or housing material Polyvinyl chloride (PVC)	Cable type Nominal attenuation Certification	Round cable 0.5Mhz €" 15Ghz 40db RoHS, REACH, UL
Connector 2 gender * Connector 1 form factor Connector 2 form factor AWG wire size Connector material Contact material		Weight & dimensions Cable length * Cable diameter Bend radius (min) Connector 1 dimensions (WxDxH) Connector 2 dimensions (WxDxH)	1.5 m 4.5 mm 4.5 cm 15.5 x 35 x 7.8 mm 12.7 x 30.8 x 7.3 mm
Connector contacts plating Magnetically shielded		Packaging data Package type	Polybag
Cable jacket material Conductor material		Packaging content Quantity per pack *	1 pc(s)
Connector shielding Connector shield material		Operational conditions	
Connector housing material Maximum data transfer rate		Operating temperature (T-T) Storage temperature (T-T)	-20 - 80 °C -25 - 85 °C
Maximum data transfer rate Product colour *	10 Gbit/s Black, Grey	Logistics data Harmonized System (HS) code	84733080



4002888369121

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.