Lindy DST-Mini XT, USB-C Laptop Mini Docking Station with Single Display (4K) or Dual Display (Full HD) and 100W Pass-Through Charging

Brand : Lindy

Product code: 43323

Product name : DST-Mini XT, USB-C Laptop Mini Docking Station with Single Display (4K) or Dual Display (Full HD) and 100W Pass-Through Charging

- Adds 2 USB Type A ports and 1 USB Type C port (5Gbps), a 4K HDMI and DP port, Gigabit Ethernet and an Audio port to a laptop
- Supports 3840x2160@30Hz for an HDMI or DP display and Full HD 1920x1080 for simultaneous use of HDMI and DP displays
- Features DisplayPort Alternate Mode
- USB Power Delivery 3.0 (100W) allows charging the laptop while using the Mini Dock
- 2 year warranty
DST-Mini XT, USB-C Laptop Mini Docking Station with Single Display (4K) or Dual Display (Full HD) and 100W Pass-Through Charging
Lindy DST-Mini XT, USB-C Laptop Mini Docking Station with Single Display (4K) or Dual Display (Full HD) and 100W Pass-Through Charging. Connectivity technology: Wired, Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery up to: 100 W. Ethernet LAN data rates: 1000 Mbit/s. Product colour: Black, Grey, Compatible memory cards: SD, Data transfer rate: 5 Gbit/s. Power source type: USB. Width: 116.5 mm, Depth: 61 mm, Height: 16 mm


Ports & interfaces

Connectivity technology *	Wired
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB Power Delivery (USB PD)	✔
USB Power Delivery revision	3.0
USB Power Delivery up to	100 W
HDMI ports quantity *	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.2
Microphone in *	✘
Combo headphone/mic port	✔
HDCP	✔
HDCP version	1.4

Network

Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	1000 Mbit/s

Performance

Card reader integrated *	✔
Compatible memory cards	SD
Data transfer rate	5 Gbit/s
HD type	4K Ultra HD
Maximum digital resolution	3840 x 2160 pixels

Performance

Maximum refresh rate	30 Hz
Product colour *	Black, Grey
Housing material	Aluminium
Certification	CE, UKCA, FCC, REACH & RoHS

Power

Power source type	USB

Operational conditions

Operating temperature (T-T)	0 - 55 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	0 - 85%

Weight & dimensions

Width	116.5 mm
Depth	61 mm
Height	16 mm
Weight	115 g

Packaging data

Quantity per pack	1 pc(s)
Package width	150 mm
Package depth	137 mm
Package height	120 mm
Package weight	150 g

Packaging content

Manual	✔

Technical details

Compliance certificates	CE, REACH, RoHS

Logistics data

Harmonized System (HS) code   84733020

4002888433235