

## 3.7kW Single-Phase Local Metered PDU, 208/230V Outlets (6-C19 & 32-C13 ) C20/L6-20P Cable 10 ft. (3.05 m) Cord, 0U Vertical

MODEL NUMBER: PDUMV20HV



### Features

- 16/20A single phase 230/208V Local Metered Power Distribution Unit / PDU (Agency derated to 16A continuous)
- Two-digit lighted meter reports combined total output current in amps
- 10ft / 3m detachable input cable with NEMA L6-20P plug
- C20 inlet accepts a variety of 16A international cordsets
- 0U 63.75in / 162cm vertical rackmount format installs using no rack spaces
- 38 total outlets (6 C19, 32 C13)
- Included plug-lock inserts ensure components remain connected and powered
- Toolless installation supported in button-mount compatible equipment racks
- Bolt-down installation brackets support installation in other racks and additional surfaces

### Highlights

- Local metered single phase 16A 208/230V 0U 63.75in / 162cm vertical rackmount PDU
- Two-digit meter reports output current in amps
- 10ft / 3m detachable input cable with NEMA L6-20P plug
- C20 inlet accepts a variety of 16A international cordsets
- 38 output receptacles (6 C19, 32 C13)
- Ready for immediate toolless 0U installation

### Package Includes

- PDUMV20HV 63.75 inch basic PDU
- Plug-lock inserts (6 C20, 32 C13)
- Spare installation buttons, 2.9 mm/4.6 mm
- 10-ft. (3.05 m) detachable C19-to-L620P input cordset
- Mounting hardware
- Owner's Manual

## Specifications

| OVERVIEW                       |                                      |
|--------------------------------|--------------------------------------|
| UPC Code                       | 037332139344                         |
| PDU Type                       | Local Metered                        |
| INPUT                          |                                      |
| Input Phase                    | Single-Phase                         |
| PDU Input Voltage              | 208; 230                             |
| Recommended Electrical Service | Single-phase 16/20A 230/208V service |

|  |  |
|--|--|
| Maximum Input Amps                           | 16   |
| Maximum Input Amps Details                   | Agency de-rated to 16A continuous  |
| Input Connection Type                        | L6-20P detachable cordset, C20 inlet available   |
| PDU Plug Type                                | NEMA L6-20P; IEC-320 C20   |
| Input Cord Length (ft.)                      | 10   |
| Input Cord Length (m)                        | 3.05   |
| <b>OUTPUT</b>                                |  |
| Output Capacity Details                      | 3.68kW (230V), 3.33kW (208V) / 16A total capacity; 16A max per C19 outlet; 12A (10A CE) max per C13 outlet |
| Frequency Compatibility                      | 50 / 60 Hz   |
| Output Receptacles                           | (32) C13; (6) C19  |
| Output Nominal Voltage                       | 208/230V   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Front Panel LCD Display                      | Digital meter reports PDU output current in amps   |
| <b>SURGE / NOISE SUPPRESSION</b>             |  |
| Automatic Shut-Off                           | No   |
| <b>PHYSICAL</b>                              |  |
| Material of Construction                     | Aluminum   |
| Form Factors Supported                       | 0u vertical installation in equipment racks, plus under-counter and wallmount                              |
| PDU Form Factor                              | Vertical (0U)  |
| Shipping Dimensions (hwd / in.)              | 5.00 x 3.50 x 65.50  |
| Shipping Dimensions (hwd / cm)               | 12.70 x 8.89 x 166.37  |
| Shipping Weight (lbs.)                       | 9.50   |
| Shipping Weight (kg)                         | 4.31   |
| Unit Dimensions (hwd / in.)                  | 3.750 x 2.250 x 63.750   |
| Unit Dimensions (hwd / cm)                   | 162 x 5.7 x 9.5  |
| Unit Weight (lbs.)                           | 5.20   |
| Unit Weight (kg)                             | 2.36   |
| <b>ENVIRONMENTAL</b>                         |  |
| Operating Temperature Range                  | 32° to 104°F (0° to 40°C)  |
| Storage Temperature Range                    | -22° to 122°F (-30° to 50°C)   |
| Relative Humidity                            | 0% to 95% non-condensing   |
| Operating Elevation (ft.)                    | 0-10,000   |

|                                     |  |
|-------------------------------------|--|
| Operating Elevation (m)             | 0-3000   |
| <b>STANDARDS &amp; COMPLIANCE</b>   |  |
| Product Certifications              | IEC 62368-1; RETIE (Colombia); GOST (Russia); NOM (Mexico) |
| Product Compliance                  | RoHS; CE (Europe); EAC (Belarus, Kazakhstan, Russia); UKCA |
| <b>WARRANTY &amp; SUPPORT</b>       |  |
| Product Warranty Period (Worldwide) | 2-year limited warranty                                    |