

## **AXIS T91E61 Wall Mount**

## Made for fixed dome cameras



- > Small and robust design
- > For indoor and outdoor use
- > Impact and corrosion resistant

AXIS T91E61 Wall Mount is specially designed for Axis xed dome network cameras. Neat design for both indoor and outdoor installations.

Thanks to its impact-resistant and outdoor proven material, AXIS T91E61 Wall Mount suits all environments where Axis xed dome cameras are used in. It is designed for being mounted with Axis cameras and gives a discreet look due to its small form factor.

It is compatible with all Axis xed dome pendant kits with a 1.5" NPS thread and can also be installed on AXIS T94R01P Conduit Back Box to enable use of cable protection conduits. With accessories it is possible to use the mount on poles, corners and on the door of AXIS T98A-VE Cabinet Series.

AXIS T91E61 has the same hole pattern as the wall mount for outdoor xed box Axis cameras to enable an easy switch. The compatible conduit back box has the same hole pattern as AXIS T91A/T91B and AXIS T91D61 Wall Mounts, making sure that swapping two Axis cameras is as easy as possible.

Moreover, it is possible to run the cable externally by using one of the four cut-outs in the base of the wall mount.

## **Technical Specifications - AXIS T91E61 Wall Mount**

Models	AXIS T91E61 Wall Mount
General	
Supported products	AXIS T94B01D Pendant Kit (AXIS M3004-V/M3005-V), AXIS T94F01D Pendant Kit (AXIS M3006-V/M3007-P/M3007-PV and AXIS M3024-LVE/M3025-VE/M3026-VE/M3027-PVE), AXIS T94F02D Pendant Kit (AXIS M3024-LVE/M3025-VE/M3026-VE/M3027-PVE), AXIS T94K01D Pendant Kit (indoor models of AXIS P32/P33/035), AXIS T94M01D Pendant Kit (outdoor models of AXIS 035), AXIS T94T01D Pendant Kit (outdoor models of AXIS P32)
Maximum load	10 kg (22 lb)
Cable routing	Internal Back: Cable hole Side: Cut outs
Environment	Indoor/Outdoor

Casing	Powder coated, chromated aluminum Color: White NCS S 1002-B Interface: 1.5" NPS
Compliance	RoHS, REACH, CE
Approvals	IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, EN 50581, UL 50E, IEC 62262 IK10, IEC 60721-3-4 (Class 4M4), NEMA 250 Type 4X
Dimensions	80 x 161 x 120 mm (3.1 x 6.3 x 4.7 in)
Weight	525 g (1.15 lb)
Included accessories	Installation Guide
Optional accessories	AXIS T94R01P Conduit Back Box, AXIS T91A47 Pole Mount, VT Corner Mount WCWA, Network Cable Coupler IP66 (requires AXIS T94R01P Conduit Back Box)
Warranty	Axis 3-year warranty, see www.axis.com/warranty

More information is available at www.axis.com

