

SPECIFICATION SHEET

ZEBRA 3600 ULTRA-RUGGED SERIES:
DS3608-HP/DS3678-HP CORDED AND CORDLESS HIGH PERFORMANCE 2D IMAGER



ZEBRA

DS3608-HP/DS3678-HP Ultra-Rugged Scanner

Unstoppable performance on 1D/2D barcodes at longer distances — plus OCR, photos and documents

Every day, workers in your warehouse and on the manufacturing plant floor scan thousands of barcodes to ensure product quality and on-time order delivery. Their productivity depends on the quality of the scanner you put in their hands. When your workers need to capture 1D and 2D barcodes, OCR, photos and documents, with the corded DS3608-HP and cordless DS3678-HP High Performance imagers, you can give them the best — unmatched rugged design, unmatched scanning performance and unrivaled manageability. Advanced scanning delivers lightning-fast capture of any 1D or 2D barcode to nearly 7 ft./2.1 m away, regardless of whether it is printed on a label in virtually any condition, or displayed on a screen. The ultra-rugged design is practically indestructible — ideal for punishing environments. The scanners couldn't be easier and less time-consuming to deploy and manage. And when it comes to cordless technology, the DS3678-HP is loaded with Zebra-only features that put it in a class of its own. The DS3608-HP/DS3678-HP — the unstoppable performance you need to maximize workforce productivity and throughput in your operations.



Superior scanning performance on any 1D/2D barcode, in any condition

The advanced imager reads 1D and 2D barcodes displayed on a screen or printed on a label faster and with 30 percent more working range than similar models in this class, delivering extraordinary productivity. Workers get first time capture of virtually every barcode, even if it is damaged, dirty, poorly printed or under shrinkwrap.

Ultra-rugged — the most indestructible design in its class

The DS3608-HP/DS3678-HP is our most rugged scanner yet, with the highest drop, tumble and sealing specification in its class. The DS3608-HP/DS3678-HP is built to survive an 8 ft./2.4 m drop to concrete — 23 percent more durable than any other scanner in this class.

The DS3608-HP/DS3678-HP operates reliably after 5,000 tumbles, simulating the real-world tumbling that occurs with a drop. Both models are dustproof, sprayproof and waterproof to IP67 — they can be sprayed down with jetting water and even submersed in water.

Beyond barcodes: capture OCR, photos and documents

With Zebra's intelligent document capture we take photos and sharpen and correct the images so they are easier to read. And support for multiple OCR fonts enables fast and easy transfer of data.

Easy management with our complimentary industry-best tools

Remotely configure scanners, upgrade firmware, format data properly for your back end and monitor PowerPrecision+ battery statistics and more with 123Scan and Scanner Management Service (SMS).

Multi-code captures and processes up to 20 barcodes simultaneously

Many labels have multiple barcodes your workers need to capture. Now, one press of the trigger captures the right barcodes and applies the unique data format required for each one for instant transmission to your backend systems — all with complete control over the order barcodes are processed.

Faster pick-list processing

Users can easily select and capture an individual barcode from any pick list.

Extreme temperature rating

Built to handle extreme cold, heat and humidity, you can use these scanners anywhere — even in the freezer*.

A Bluetooth model in a class of its own for superior cordless freedom

Bluetooth 4.0 (Low Energy) provides lightning fast wireless communication and maximum energy efficiency.

Our Zebra Wi-Fi Friendly Mode eliminates the wireless interference that Bluetooth devices can create in your Wi-Fi environment.

The 'go anywhere' rugged cradle offers superior versatility and durability. The DS3678-HP is the only scanner in its family to offer a cradle with IP65 sealing. And its industrial charging contacts withstand 250,000 insertions.

The first-in-its-class battery 'charge gauge' and Bluetooth status LED make it easy to monitor battery power as well as Bluetooth connectivity.

The PowerPrecision+ battery delivers the ultimate in battery power and management. You get more than twice the amount of scans per charge than with competitive models — more than 100,000 scans

SPECIFICATION SHEET

ZEBRA 3600 ULTRA-RUGGED SERIES:
DS3608-HP/DS3678-HP CORDED AND CORDLESS HIGH PERFORMANCE 2D IMAGER

per charge, so workers can scan more items over a longer period of time. You also get visibility into a wealth of battery health-related data, including charge cycles consumed, current battery status and a State of Health meter, which identifies if batteries are healthy and holding a full charge or ready for retirement.

Three flexible feedback modes

Mix and match the feedback modes that are ideal in your environment — vibration, red and green LEDs located in an area where they are always easy to see, plus the traditional loud beep tone.

Instantly connect to your Industrial Ethernet network

Zebra's Network Connect for Automation delivers a seamless connection between DS3608-HP/DS3678-HP scanners and a manufacturer's Industrial Ethernet network without the need for

third party conversion equipment. The solution eliminates vulnerability points, improves security, reduces complexity and is compatible with every Zebra 3600 Series scanner.

DataCapture DNA

Zebra's DataCapture DNA is a technology platform of highly intelligent firmware, software, utilities and apps exclusively engineered for Zebra scanners. Leveraging more than 35 years of Zebra's industry expertise, DataCapture DNA delivers innovations that give our best-in-breed imagers greater intelligence and simplicity. When combined with the unstoppable performance found in every 3600 Series ultra-rugged scanner, DataCapture DNA turns Zebra's 3600 Series scanners into powerful tools that help to resolve tomorrow's data capture challenges today — and help your workers get more done each day.

The Zebra 3600 Ultra-Rugged Scanner Series

This family of scanners offers a model to meet virtually every need in warehousing and manufacturing:

- **LI3608-SR/LI3678-SR:**
Standard range 1D barcode capture
- **LI3608-ER/LI3678-ER:**
All-range 1D barcode capture
- **DS3608-SR/DS3678-SR:**
Standard range scanning of 1D and 2D barcodes
- **DS3608-HP/DS3678-HP:**
High performance scanner captures 1D/2D barcodes over longer distances, plus OCR, photos and documents
- **DS3608-HD/DS3678-HD:**
Captures high-density 1D/2D barcodes
- **DS3608-DP/DS3678-DP:**
Capture of Direct Part Marks (DPM)
- **DS3608-ER/DS3678-ER:**
All-range 1D/2D barcode capture


The DS3608-HP/DS3678-HP — Advanced capture of 1D/2D barcodes, documents, images and more in an ultra-rugged scanner that redefines reliability.

For more information, visit www.zebra.com/DS36x8-HP or access our global contact directory at www.zebra.com/contact

SPECIFICATION SHEET

ZEBRA 3600 ULTRA-RUGGED SERIES:
DS3608-HP/DS3678-HP CORDED AND CORDLESS HIGH PERFORMANCE 2D IMAGER

DS3608-HP/DS3678-HP Specifications Chart

PHYSICAL CHARACTERISTICS	
Dimensions	Corded: 7.3 in. H x 3.0 in. W x 5.2 in. D 18.5 cm H x 7.6 cm W x 13.2 cm D Cordless: 7.3 in. H x 3.0 in. W x 5.6 in. D 18.5 cm H x 7.6 cm W x 14.2 cm D
Weight	Corded: 10.9 oz./309 g Cordless: 14.5 oz./411 g
Input Voltage Range	Host powered: 4.5 VDC min., 5.5 VDC max. External power supply: 11.4 VDC min., 12.6 VDC max.
Operating Current	DS3608-HP (corded): 360 mA (RMS typical)
Standby Current	DS3608-HP (corded): 100 mA (RMS typical)
Color	Industrial Green
Supported Host Interfaces	USB, RS232, Keyboard Wedge Industrial Ethernet: EtherNet/IP, Profinet, Modbus TCP & Std TCP/IP
Battery	 PowerPrecision+ 3100 mAh Li-Ion rechargeable battery
User Indicators	Direct decode indicator; LEDs; beeper; vibration
PERFORMANCE CHARACTERISTICS	
Scans per Full Charge	100,000+
Illumination	Two (2) warm white light LEDs
Aimer	655 nm laser
Imager Field of View	Horizontal: 31°, Vertical: 23°
Image Sensor	1,280 x 960 pixels
Minimum Print Contrast	15% minimum reflective difference
Skew/Pitch/Roll	Skew: ± 60° Pitch: ± 60° Roll: ± 360°
DECODE CAPABILITIES**	
1D	Code 39, Code 128, Code 93, Codabar/NW7, Code 11, MSI Plessey, UPC/EAN, 1 2 of 5, Korean 3 of 5, GSI DataBar, Base 32 (Italian Pharma)
2D	PDF417, Micro PDF417, Composite Codes, TLC-39, Aztec, DataMatrix, MaxiCode, QR Code, Micro QR, Chinese Sensible (Han Xin), Postal Codes
OCR	OCR-A/B, MICR-E13B, US Currency Serial Number
IUID Support	Supports IUID parsing, the ability to read and separate IUID fields per application requirements
USER ENVIRONMENT	
Operating Temp.	Corded: -22° F to 122° F/-30° C to 50° C Cordless: -4° F to 122° F/-20° C to 50° C
Storage Temp.	-40° F to 158° F/-40° C to 70° C
Humidity	5% to 95% non-condensing
Drop Specification	Withstands multiple 8.0 ft./2.4 m drops to concrete














USER ENVIRONMENT (CONTINUED)	
Tumble Specification	5000 tumbles @ 3.3 ft. (1 m)
Sealing	Scanner: IP65 and IP67 FLB cradle: IP65
ESD	Per EN61000-4-2, ±25 KV air discharge, ±10 KV direct discharge, ±10 KV indirect discharge
Explosion Protection	Explosion-protected version available from BARTEC. For more information, visit www.Bartec.de/en
Ambient Light Immunity	0 to 10,037 Foot Candles/0 to 108,000 Lux (direct sunlight)
UTILITIES AND MAINTENANCE	
123Scan	Programs scanner parameters, upgrades firmware, provides scanned barcode data and prints reports. For more information, visit www.zebra.com/123Scan
Scanner SDK	Generates a fully-featured scanner application, including documentation, drivers, test utilities and sample source code. For more information, visit www.zebra.com/windowsSDK
Scanner Management Service (SMS)	Remotely manages your Zebra scanner and queries its asset information. For more information, visit www.zebra.com/sms
Network Connect	Seamlessly connects 3600 Series scanners directly to your Industrial Ethernet network without any third party conversion equipment. For more information, visit www.zebra.com/NetworkConnect
WIRELESS CONNECTIVITY	
Bluetooth Radio	Bluetooth Class 1, Version 4.0 (LE), serial port (SPP) and HID profiles
Data Rate	3 Mbit/s (2.1 Mbit/s) for Classic Bluetooth 1 Mbit/s (0.27 Mbit/s) for Low Energy
Radio Range	Direct line of sight in open air: Class 1: Minimum 300 ft. (100.0 m); Class 2: Minimum 30 ft. (10.0 m)
REGULATORY	
Environmental	RoHS EN 50581: 2012
Electrical Safety	EU Safety: EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011 + AC 2011 + A2: 2013; International Safety: IEC 60950-1: 2005 + A1: 2009 + A2: 2013; US/Canada Safety: UL 60950-1, second edition, CAN/CSA-C22.2 No. 60950-1-07
Laser/LED Safety	International LED Safety: IEC 62471: 2006 (Ed.1.0); EN 62471: 2008 (LED); UL, VDE and CU recognized laser component
EMI/RFI	IT Emissions: EN 55022: 2010/AC: 2011 (Class B); IT Immunity: EN 55024: 2010; Heavy Industrial: EN 61000-6-2: 2005/AC:2005; Harmonic Current Emissions: EN 61000-3-2: 2006 + A1: 2009 + A2: 2009 (Class B); Voltage Fluctuation and Flicker: EN 61000-3-3: 2013; Medical Electrical Equipment: EN 60601-1-2: 2007/AC: 2010, IEC 60601-1-2: 2007 (Modified); Radio Frequency Devices: 47 CFR Part 15, Subpart B, Class B; Digital Apparatus: ICES-003 Issue 5, Class B

SPECIFICATION SHEET

ZEBRA 3600 ULTRA-RUGGED SERIES:

DS3608-HP/DS3678-HP CORDED AND CORDLESS HIGH PERFORMANCE 2D IMAGER

DS3608-HP/DS3678-HP Specifications (continued)

DATACAPTURE DNA	
PRODUCTIVITY TOOLS	
 Intelligent Document Capture	 PRZM Intelligent Imaging
 Multi-code Data Formatting	 Wi-Fi™ Friendly Mode
 Preferred Symbol	
MANAGEMENT TOOLS	
 123Scan	 Remote Management
 PowerPrecision+	
VISIBILITY TOOLS	
 Remote Diagnostics	 ScanSpeed Analytics
DEVELOPMENT TOOLS	
 Scanner Control Application	 Software Development Kit
 Scan-to-Connect	

For more information about DataCapture DNA and its applications, please visit www.zebra.com/datacapturedna

DECODE RANGES	
Symbology/Resolution	Near/Far
Code 128: 5 mil	6.0-14.0 in./15.2-35.6 cm
Code 128: 20 mil	5.0-45.0 in./12.7-114.3 cm
Code 128: 40 mil	2.8-80 in./71-203.2 cm
Datamatrix: 7.5 mil	7.0-11.0 in./ 17.8-27.9 cm
Datamatrix: 10.0 mil	6.0-15.0 in./15.2-38.1 cm

WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the DS3608-HP/DS3678-HP is warranted against defects in workmanship and materials for a period of: Scanner and Cradle: thirty-six (36) months, Battery twelve (12) months from the date of shipment. For complete warranty statement, go to: <http://www.zebra.com/warranty>

RECOMMENDED SERVICES

Zebra *OneCare* Select: Zebra *OneCare* Essential

* Heated scanner holder accessory recommended to reduce condensation on the outside of scan window when moving in and out of freezers.

** Refer to Product Reference Guide for complete list of symbologies.



NA and Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
contact.apac@zebra.com

EMEA Headquarters
zebra.com/locations
contact.emea@zebra.com

Latin America Headquarters
+1 847 955 2283
la.contactme@zebra.com