

10 pack HPE J4858C Compatible SFP Module - 1000BASE-SX - 1GbE Multi Mode Fiber Optic Transceiver - 1GE Gigabit Ethernet SFP - LC 550m - 850nm - DDM HPE 1400, 1700, 1820

Product ID: J4858C10PKST



The J4858C10PKST is a ten-pack of our HPE J4858C compatible fiber transceiver module that has been designed, programmed and tested to work with HPE brand switches and routers. It delivers dependable 1 GbE connectivity over fiber cable, for 1000BASE-SX compliant networks, with a maximum distance of up to 550 m (1804 ft).

Technical Specifications:

- Wavelength: 850 nm
- Maximum Data Transfer Rate: 1.25 Gbps
- Type: Multi Mode Fiber
- Connection Type: LC Connector
- Maximum Transfer Distance: 550 m (1804 ft)
- MTBF: 3,381,761 hours
- Power Consumption: Less than 1.3 Watts
- Digital Diagnostics Monitoring (DDM): Yes

This SFP fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.

Certifications, Reports and Compatibility



Applications

- Replacing defective or damaged SFP modules in HP switches and routers
- Expand your network to remote segments

Features

- **100% HPE J4858C COMPATIBLE:** 10 pack SFPs work with HPE switches like 1400, 1700, 1820, 2520, 2530 and others
- **TECHNICAL SPECS:** 1000BASE-SX 1Gbps Multi Mode (MMF) LC Connector 850nm Digital Diagnostic Monitoring (DDM) Distances up to 550m (1804ft)
- **TESTED FOR OEM HOST COMPATIBILITY:** Hot-swappable in HPE routers and switches; DDM support reports the transceiver's status to most SNMP network management tools
- **WORKS WITH MSA COMPLIANT SWITCHES:** Also works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules
- **THE IT PRO'S CHOICE:** Designed and built for IT Professionals, this SFP module is backed for life (lifetime of module, not network switch), including free lifetime 24/5 multi-lingual technical assistance

Hardware

| | |
|--------------------|-------------------------|
| Warranty | Lifetime |
| Compatible Brand | HPE |
| WDM | No |
| Industry Standards | IEEE 802.3z 1000BASE-SX |

Performance

| | |
|----------------------------|-----------------|
| Maximum Data Transfer Rate | 1.25 Gbps |
| Max Transfer Distance | 550 m (1804 ft) |
| Type | Multi Mode |
| Wavelength | 850nm |

| | |
|------------------------------|--------------------|
| Fiber Operating Mode | Half/Full-Duplex |
| DDM | Yes |
| Compatible Networks | 1000 Mbps (1 Gbps) |
| MTBF | 3,381,761 hours |
| Power Consumption (In Watts) | < 1 W |

Connector(s)

| | |
|-----------------------|---------------------------|
| Local Unit Connectors | 1 - Fiber Optic LC Duplex |
|-----------------------|---------------------------|

Special Notes / Requirements

| | |
|------|--|
| Note | For use in Gigabit fiber networking equipment and media converters |
|------|--|

Environmental

| | |
|-----------------------|----------------------------|
| Operating Temperature | 0C to 70C (32F to 158F) |
| Storage Temperature | -40C to 85C (-40F to 185F) |
| Humidity | 30~75% RH |

Physical Characteristics

| | |
|-------------------|------------------|
| Product Length | 2.2 in [56.6 mm] |
| Product Width | 0.5 in [12.5 mm] |
| Product Height | 0.5 in [1.3 cm] |
| Weight of Product | 0.6 oz [16.0 g] |

Packaging Information

| | |
|---------------------------|------------------|
| Package Length | 7.1 in [18.1 cm] |
| Package Width | 5.0 in [12.7 cm] |
| Package Height | 1.4 in [35.0 mm] |
| Shipping (Package) Weight | 7.6 oz [215.0 g] |

What's in the Box

Included in Package 10 - SFP transceivers

**Product appearance and specifications are subject to change without notice.*