

AXIS T91L61 Wall-and-Pole Mount

For quick wall and pole installations

Designed for Axis PTZ and multisensor cameras, AXIS T91L61 Wall-and-Pole Mount can quickly connect power and data to the camera through a built-in Ethernet cable with an IP66 RJ45 connector. The ability to choose between an RJ45 or IDC (insulation-displacement contact) connector makes installation flexible. AXIS T91L61 is also suitable for corner mounting with an optional accessory. Thanks to its impact-resistant and outdoor-proven material, it can be used in both indoor and outdoor environments. Note that this mount is not intended for inverted installations.

- > [Flexible installation using the IDC connector](#)
- > [Built-in IP66 RJ45 connector](#)
- > [Suitable for wall and pole mounting](#)
- > [Protection against impact, water, dust and corrosion](#)



AXIS T91L61 Wall-and-Pole Mount

General		Impact
Supported products	AXIS Q60 Series AXIS Q61 Series AXIS P55 Series AXIS P56 Series AXIS Q37 Series	IEC 62262 IK10
Casing	Material: Powder-coated aluminum casing Color: White NCS S 1002-B	Dimensions 280 x 174 x 152 mm (11 x 7 x 6 in)
Sustainability	PVC free	Weight 1.85 kg (4 lb)
Connectors	Out: IP66 RJ45 Ethernet (male) In: RJ45 Ethernet (female), IDC	Maximum load 30 kg (66 lb)
Environment	Indoor Outdoor	Cable routing Back: Cable hole Bottom: 3/4" Conduit entrance
Operating conditions	-50 °C to 65 °C (-58 °F to 149 °F) Humidity 10–100% RH (condensing)	Included accessories Installation Guide
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	Optional accessories AXIS ACI Conduit Adapters AXIS T91A64 Corner Bracket AXIS Steel Straps TX30 570 mm AXIS Steel Straps TX30 1450 mm For more accessories, see www.axis.com
Approvals	Safety IEC/EN/UL 60950-1, IEC/EN/UL 60950-22 Environment IEC 60721, IEC 60721-4 Class 4M3, MIL-STD 810G 509.5, IP66, NEMA 250 Type 4X, RoHS, WEEE	Warranty 3-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility