

AXIS T94N01G Pole Mount

For sturdy installations in harsh environments

The high-quality AXIS T94N01G Pole Mount is designed for use with Axis positioning cameras, positioning units and AXIS T98A cabinet series. It is easily adjustable to fit poles of between 100-410 mm (4-16 in) in diameter. AXIS T94N01G is made from marine-grade (SUS 316L) stainless steel and is suitable for marine, underground, and other high corrosion applications. The pole mount has an IK10 rating for impact resistance, which safeguards it against vandalism. It features a closed back and a cable gasket for protection against insect infestation.

- > [Marine-grade stainless steel \(SUS316L\) for use in harsh outdoor environments](#)
- > [Impact-resistant to prevent vandalism \(IK10\)](#)
- > [Cable gasket to prevent insect infestation](#)
- > [Robust and safe](#)
- > [Suitable for Axis positioning cameras and positioning units](#)



AXIS T94N01G Pole Mount

General	
Supported products	AXIS T94J01A Wall Mount AXIS T91D62 Telescopic Parapet Mount AXIS T98A-VE Cabinet Series
Material	Powder-coated stainless steel SUS 316L Color: white NCS S 1002-B
Sustainability	PVC free
Environment	Indoor Outdoor
Storage conditions	-45 °C to 70 °C (-49 °F to 158 °F)
Approvals	Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 Environment NEMA 250 Type 4x, IEC 62262 IK10, RoHS, REACH, WEEE
Dimensions	49 x 231 x 226 mm (1.9 x 9.1 x 8.9 in)
Weight	1.7 kg (3.7 lb)
Maximum load	25 kg (55.1 lb)
Cable routing	Back: cable hole
Included accessories	Installation Guide Stainless steel straps 1450 mm (57 in), 3 pieces Insect-proof cable gasket for 4 cables Gasket C M20 Set screw
Optional accessories	Stainless steel straps 700 mm (28 in), 1 pair Stainless steel straps 570 mm (22 in), 1 pair For more accessories, see axis.com
Warranty	Axis 3-year warranty, see axis.com/warranty
Environmental responsibility: axis.com/environmental-responsibility	