



USB-C 4-in-1 Audio/Video Converter

USB 3.1 Type-C Male to HDMI/DP/VGA/DVI Female, Black

Part No.: **152600**

Easily connect a USB Type-C source with an HDMI, DP, VGA or DVI display.

The Manhattan USB-C 4-in-1 Audio/Video Converter establishes a fast, simple and convenient link between newer USB Type-C equipped media sources (computers, tablets, Smartphones, etc.) and existing HDMI, DisplayPort, VGA or DVI displays (monitors, projectors, etc.). The Manhattan USB-C 4-in-1 Audio/Video Converter is easy and quick to install — no complicated configuration or setup required. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly. Extend the service life of your equipment, and fully realize the investment and value of your HDMI, DP, VGA or DVI displays, projectors and peripherals with a Manhattan USB-C 4-in-1 Audio/Video Converter.

Features:

- 4-in-1 adapter converts USB to an HDMI, DP, VGA or DVI video and audio signal
- Offers Ultra-High-Definition (UHD) images on an HDMI monitor, projector or other display device
- Supports video resolutions up to: 3840x2160 at 30 Hz (4K) in HDMI, 4K@60Hz UHD in DP or 1920x1080 at 60 Hz in VGA or DVI
- Compliant with DisplayPort 1.2 Alternate Mode (DP Altmode)
- Plug and Play; requires no external power supply
- Compatible with all USB Type-C, DP Alt mode and Power Deliver 2.0 supported desktops, notebooks and tablets including Apple MacBook, Chromebook Pixel and more
- Compact, portable design; perfect for traveling and connecting to any display
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Three-Year Warranty

Specifications:

Standards and Certifications

- USB 3.1
- HDMI
- HDCP 1.4
- CE
- FCC
- RoHS2
- WEEE

General

- Video Resolutions: 640 x 480, 800 x 600, 1024 x 768, 1920 x 1080, 1920 x 1200, 3840 x 2160 at 30 Hz, 4K@60Hz
- 32 AWG connectors
- Shielding: Mylar and aluminum
- Withstanding voltage: 300 V DC
- Insulation resistance: 5 MOhm
- Conductive resistance: 10 Ohm
- Supports one output at a time
- If multiple connections are made, port priority will be DP>HDMI>DVI>VGA
- Note: DVI and VGA do not support Audio

Connections

- USB Type-C 24-pin, male
- HDMI 19-pin, female
- DP 20-pin, female
- DVI Single Link, 29-pin, female
- VGA 15-pin, female
- Shielded

Physical

- 32 AWG cable gauge
- Mylar and aluminum shielding
- Thermal plastic casing
- Length: 8 cm (3 in.)
- Weight: 31 g (1.1 oz.)
- Shielded
- Housing: ABS plastic

Operating Environment

- Operation Temperature: 32 – 122°F (0 – 50°C)
- Storage Temperature: -22 – 176°F (-30 – 80°C)
- Humidity (noncondensing): 5 – 90%

System Requirements

- Windows 8.1/10 or Linux or Mac 10.10.5 or above

Package Contents

- USB-C 4-in-1 Audio/Video Converter

•

