



SuperSpeed USB-C to 7-in-1 Docking Station

USB 3.1 Type-C Male to HDMI, Mini DP or VGA, Three USB 3.0 Type-A Ports, USB-C PD Port, Gigabit RJ45 Port, SD Card Reader, and 3.5 mm Audio Port; Aluminum, Gray

Part No.: **152808**

Easily connect a USB Type-C device to an HDMI, Mini DP or VGA display, USB peripherals, Network and SD memory card.

The Manhattan SuperSpeed USB-C to 7-in-1 Docking Station establishes a fast, simple and convenient link between newer USB Type-C-equipped media sources (computers, tablets, Smartphones, etc.) and an existing HDMI/Mini DP/VGA display (monitors, projectors, etc.), in either mirror- or extended-display mode. Create a mini-workstation by adding any USB 3.0 (and earlier) peripheral, such as a mouse, keyboard, hub, external memory device and more, with the integrated USB-A ports, Gigabit network connection, 3.5 mm Stereo and SD and Micro SD card slot, all while charging your device through the USB-C port.

The Manhattan SuperSpeed USB-C to 7-in-1 Docking Station is easy and quick to install. No complicated configuration or setup is required to enhance the functionality of your Type-C device. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and work spaces neat and orderly.

Features:

- Multi-function docking station connects a USB Type-C device to an HDMI, Mini DP or VGA display, three USB 3.0 Type-A ports, a 10/100/1000 Mbps port, a 3.5 mm stereo port, a USB-C power port and an SD Card Reader
- Delivers Ultra-High-Definition (UHD) 4K@30Hz video and audio over HDMI or Mini DP connection or HD 1080p video over VGA connection
- Mirror or extended-display modes support video resolutions up to 1080p@60Hz or 3840x2160 at 30 Hz (4K) Full UHD; Mac only supports mirror mode
- One Gigabit Ethernet (10/100/1000) port for faster downloads, media streaming and gaming
- Three USB 3.0 Type-A ports to connect mice, keyboards or portable memory devices (and more) or to charge and sync a portable electronic device
- USB-A SuperSpeed ports offer 5 Gbps data transmission speeds; BC1.2 port charges

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

up to 7.5 W (5 V / 1.5 A)

- Easy access to media and content management with read/write/copy Micro SD and SD slots; supports automatic card detection and data transfer speeds up to 90 Mbps
- USB-C Power Delivery (PD) port for a maximum of 60 W (20 V at 3 A) to connected devices
- USB-C port provides 5 Gbps data transmission
- 3.5 mm jack for high-quality stereo sound; both mic (audio input) and headphone (audio output)
- Aluminum housing makes this durable converter the perfect desktop or travel companion
- Compatible with all USB-C DP-Alt-Mode-supported desktops, notebooks and tablets including Apple MacBook, Chromebook, Pixel and more
- Compliant with DisplayPort 1.2 Alternate Mode (DP Alt Mode)
- Plug and Play
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Three-Year Warranty

Specifications:

Standards and Certifications

- USB 3.1
- HDMI
- HDCP 1.4
- CE
- FCC
- RoHS2
- WEEE

General

- Video Resolutions: 640 x 480, 800 x 600, 1024 x 768, 1920 x 1200, 1080p, 3840 x 2160p at 30 Hz, 4K
 - USB-A ports: 5 Gbps
 - Supported flash cards: SD / SDHC / SDXC / EXTREME SD / EXTREME II SD / EXTREME III SD / ULTRA SD / ULTRA II SD / ULTRA II SD P PLUS / SD-ULTRA-X / ULTRA SPEED SD / SD PRO / SD ELITE PRO / HS SD / MMC / MMC 4.0 / HS MMC / HS RS MMC / RS MMC / RS MMC 4.0 / MMC Mobile
 - Supported flash cards: SD, SDHC and SDXC; up to 128 GB
- Transfer speed: up to 90 Mbps
- 24-AWG cable gauge
 - Bus powered
 - USB-C PD Charging Port: 60 W (20 V at 3 A)
 - USB-A Charging: 10 W (5 V at 2 A)
- One BC 1.2 port: 7.5 W (5 V at 1.5 A)
- Two ports share: 5 W (5 V at 1 A)
- Mylar and aluminum shielding
 - Withstanding voltage: 300 VDC

- Insulation resistance: 10 MOhm
- Conductive resistance: 5 Ohm

Connections

Input:

- One USB Type-C 24-pin, male

Outputs:

- One HDMI 19-pin, female
- One Mini DisplayPort 20-pin female
- One VGA 15-pin female
- One 10/100/1000 Mbps RJ45, female
- Three USB Type-A 4-pin, female
- One SD memory slot
- One Micro SD memory slot
- One 3.5mm Stereo, female
- One USB-C 24-pin, Power Delivery, female

Physical

- Housing: 137 X 75 x 17 cm (5.4 x 3 x 0.7 in.)
- Cable Length: 20 cm (8 in.)
- Weight: 198 g (7 oz.)
- Housing: Aluminum

Operating Environment

- Operation Temperature: 0 – 45°C (32 – 113°F)
- Storage Temperature: -10 – 70°C (14 – 158°F)
- Humidity (noncondensing): 10 – 90%

System Requirements

- Windows XP/Vista/7/8.1/10 or Linux or Mac 10.7.1 or above

Package Contents

- SuperSpeed USB-C to 7-in-1 Docking Station
- Quick Instruction Guide



