

IMC 200/2000 Series

Industrial PoE+ Media and Rate Converters



Powering remote devices

Allied Telesis IMC200/2000 Series Industrial Media Converters (IMCs) are ideal for powering remote devices, such as IP phones, video cameras and wireless Access Points (APs), which are more than 100m from a Power over Ethernet (PoE) switch. Each IMC can provide up to 70W of PoE.

The 2000T/SP and the 2000TP/SP each feature a 10/100/1000T twisted-pair port, and an SFP port which supports and auto detects 100X and 1000X optics. No switch configuration is needed. Allied Telesis offers a wide variety of SFPs featuring multimode, single mode and BiDi optics.

Models with a fixed fiber-optic port are available with SC or LC connectors. With these, you can achieve distances up to 2 km (100Mps) or 550 m (1000Mps). With the SFP model, you can achieve greater distances using a long-range SFP.

In addition to transmitting data, the twisted-pair port also injects power down the cable, allowing a remote PoE powered device to operate without any additional power source. All PoE+ devices (IEEE802.3at compliant) are supported. All PoE+ devices support 802.3at, PoE+, LTPoE++ and 4-pair. The PC200x PoE+ Series can deliver up to 70W of power to the remote device.

Remote Power Cycle

The IMC200/2000 Series supports the Remote Power Cycle feature. This allows a remote administrator to log in to the host switch device and disable the switch port to which the IMC is attached, causing the PoE+ device to lose power. This allows administrators to reset remote devices without physically going to the location.

Jumbo frame support

Many backbone switch products support the industry-standard IEEE 802.1Q specification for Virtual LANs (VLANs) which sends extra-long data packets on the network. The IMC200/2000 Series are fully compatible with these long packets, enabling them to be used in modern networks.

Smart MissingLink™ (SML)

The SML feature monitors network connections and provides a notification when a link fails, allowing administrators to quickly identify the source and location of failed links, and thus minimize downtime.

Key Features

Converts speed as well as media type

Supports 802.3at, PoE+, 30W and LTPoE+, 4-pair up to 70W

Supplies up to 70W of PoE power

Supports 100 and 1000Mbps fiber SFP modules (IMC2000/SP)

Auto MDI/MDI-X

Smart Missing Link (SML)

Remote Power Cycle

Supports up to 10K jumbo frames

Supports multi-mode fiber

4K MAC address table

Store-and-forward switching mode

Transparent to IEEE 802.1Q packets

Standalone or DIN rail mount

Fanless for silent operation

10/100/1000T Twisted-Pair Port LEDs

| LED | COLOR | DESCRIPTION |
|-----------|----------------|---|
| Left LED | Green | The port has established a link to a network device |
| | Blinking Green | Activity |
| | Off | The port has not established a link to a network device |
| PoE Power | Green | The twisted-pair port is connected to a powered device and is providing power |
| | Off | The twisted-pair port is not supplying power to the network device |

DIP Switch

| FUNCTION | POSITION | DESCRIPTION |
|---------------------|----------|---|
| SML | On | Smart MissingLink feature is enabled |
| | Off | Smart MissingLink feature is disabled |
| 100FD | Off | Auto Negotiate |
| | On | Forced 100-FD on copper |
| Remote PoE+ Control | Off | Turned off |
| | On | PoE power is forced off when fiber link goes down |

Fiber Port LEDs

| LED | COLOR | DESCRIPTION |
|------|----------------|---|
| LINK | Green | The port has established a link to a network device |
| | Blinking Green | Activity |
| | Off | The port has not established a link with a network device |

Operational Characteristics

| | |
|--------------------------------|--|
| MAC address table 1K addresses | |
| Forwarding/ filtering rate | 1,488,000pps for 1Gbps 148,880pps for 100Mbps 14,880pps for 10Mbps |
| Latency | 14.31sec (64 byte packet, 100Mbps full-duplex) |
| Maximum packet | 10,000 bytes size |

Optical Characteristics

| | |
|-------------|--|
| Wavelength | 1310 nm IMC200 (SC) 850 nm IMC2000 (SC) |
| Fiber cable | IMC2000 (SC) Up to 2 km (100Base-FX) on OM1/OM2 Up to 275 m (1000Base-SX) OM1 Up to 550 m (1000Base-SX) OM2 |
| SFP | See specific SFP, SMF datasheet at www.alliedtelesis.com |

Transmit Power

| | |
|--------------|----------------------------|
| IMC200 (SC) | Min -19 dBm Max -14 dBm |
| IMC2000 (SC) | Min -9.5 dBm Max -4 dBm |

Receive Sensitivity

| | |
|--------------|---------------------------|
| IMC200 (SC) | Min -32 dBm Max -3 dBm |
| IMC2000 (SC) | Min -17 dBm Max -3 dBm |

Power Characteristics

| | |
|---------|-------------|
| PoE | -48-57V DC |
| PoE+ | 51-57V DC |
| Non-PoE | -12--48V DC |

Power over Ethernet

| | |
|----------------|---|
| Operating mode | IEEE 802.3at, PoE+, 30W LTPoE+, 4-pair up to 70W |
| Maximum power | 70W |

Environmental Specifications

| | |
|-----------------------|--------------------------------|
| Operating temperature | -40°C to 75°C (-40°F to 167°F) |
| Storage temperature | -40°C to 85°C (-40°F to 180°F) |
| Operating altitude | Up to 3,048m (10k ft) |
| Relative humidity | 5% to 95% (non-condensing) |

Physical Characteristics

| | |
|------------------------|---|
| Dimensions (W x D x H) | 11.1 cm x 9.6 cm x 3.5 cm (4.4 in x 3.8 in x 1.4 in) |
| Weight | 0.748 kg (1.65 lb) |

Safety

| |
|--------------------------------------|
| UL 62368-1, EN 62368-1 |
| UL 60950-1 (UL mark) |
| CAN/CSA C22.2 No. 60950-1 (cUL mark) |
| EN 60950-1 (TUV mark) |
| IP30 |

Electrical Approvals and Compliances

| |
|-----------------------------|
| EMI/Emission & Stability |
| FCC Class A |
| EN55024 (immunity standard) |
| EN55032 Class A |
| EN55035 |
| VCCI Class A |
| RoHS |

Ordering Information

AT-IMC200T/SC-980
10/100/1000T to 100FX (SC), 2 km, MMF, industrial temperature, TAA compliant

AT-IMC200TP/SC-980
10/100/1000T to 100FX (SC), 2 km, MMF, industrial temperature, TAA compliant

AT-IMC2000T/SC-980
10/100/1000T to 1000SX/SC, 550 m MMF, industrial temperature, TAA compliant

AT-IMC2000TP/SC-980
10/100/1000T PoE+ to 1000SX/SC, 550 m MMF, industrial temperature, TAA compliant

AT-IMC2000T/SP-980
10/100/1000T to 100/1000X SFP, industrial temperature, TAA compliant

AT-IMC2000TP/SP-980
10/100/1000T PoE+ to 100/1000X SFP, industrial temperature, TAA compliant

Supported SFP Modules
IMC2000T/SP & IMC2000TP/SP

AT-SPTX/I
100 m, 10/100/1000T SFP, RJ-45, I-Temp

AT-SPSX/I
550 m, 1000SX SFP, LC, MMF, 850 nm, I-Temp

AT-SPSX/E
550 m, 1000SX SFP, LC, MMF, 850 nm, Ext. Temp

AT-SPEX/E
2 km, 1000EX SFP, LC, MMF, 1310 nm, Ext. Temp

AT-SPLX10/I
10 km, 1000LX SFP, LC, SMF, 1310 nm, I-Temp

AT-SPLX10/E
10 km, 1000LX SFP, LC, SMF, 1310 nm, Ext. Temp

AT-SPLX40/E
40 km, 1000LX SFP, LC, SMF, 1310 nm, Ext. Temp

AT-SPBD10
10 km, 1G BiDi SFP, LC, SMF

AT-SPBD20-xx/I
20 km BiDi GbE SMF SFP, I-Temp

AT-SPBD40-xx/I
40 km BiDi GbE SMF SFP, I-Temp

All Allied Telesis standard temp SFP's



North America Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

EMEA & CSA Operations | Incheonweg 7 | 1437 EK Rozenburg | The Netherlands | T: +31 20 7950020 | F: +31 20 7950021

alliedtelesis.com

617-000650_RevB

© 2019 Allied Telesis, Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.