

AXIS FA4115 Dome Sensor Unit

Flexible, discreet indoor 1080p varifocal dome

AXIS FA4115 is a compact varifocal dome sensor unit for discreet indoor video surveillance in stores, offices and banks. For use with an AXIS FA Main Unit, AXIS FA4115 provides a 1080p resolution and flexible viewing angles ranging from a 53° to 99° horizontal field of view. A narrower field of view enables finer details to be captured. In wide mode, more of a scene can be covered. AXIS FA4115 uses Forensic WDR (wide dynamic range) that is tuned for motion. The unit comes with a mounting bracket and an 8-m (26 ft) cable for connection to a main unit.

- > [Flexible, compact dome for indoor surveillance](#)
- > [Varifocal lens with 1080p resolution](#)
- > [99° -53° horizontal field of view](#)
- > [Forensic WDR](#)
- > [Axis Corridor Format for vertically oriented coverage areas](#)



AXIS FA4115 Dome Sensor Unit

| Camera | | General | |
|-------------------------|---|----------------------|---|
| Image sensor | 1/3" (effective) progressive scan RGB CMOS | Casing | Aluminum Plastic |
| Lens | Fixed iris, varifocal 2.8–6.0 mm, F2.0 Horizontal field of view: 99°–53° Vertical field of view: 53°–30° | Sustainability | PVC free |
| Resolution | 1920x1080 (1080p) | Operating conditions | -20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–85% RH (non-condensing) |
| Wide dynamic range | Forensic WDR | Storage conditions | -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5-95% RH (non-condensing) |
| Minimum illumination | Color: 0.2 lux | Approvals | EMC 55032 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, ICES-003 Class B, KCC KN32 Class B, KN35 Safety IEC/EN/UL 62368-1 Environment EN 50581, IEC 60529 IP3X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC 60068-2-6, IEC 60068-2-27 |
| Shutter time | 1/32500 s to 1/25 s with 50 Hz 1/32500 s to 1/30 s with 60 Hz | Dimensions | Height: 50 mm to 70 mm (2 in to 2 13/16 in) ø 88 mm (3 8/16 in) |
| Camera angle adjustment | Pan: 360° Tilt: 0° to 90° Rotation: 360° | Weight | 112 g (0.25 lb) |
| Frame rate | Max 25/30 fps (50/60 Hz) | Required hardware | AXIS FA Main Unit |
| | | Included accessories | 8-m (26 ft) black cable, mounting brackets Installation Guide |
| | | Optional accessories | AXIS F7315 Cable White 15 m |
| | | Warranty | Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty |

Environmental responsibility:

axis.com/environmental-responsibility