

Composite to VGA Video Converter - NTSC and PAL - 1920x1200 - Composite Video Scaler - S Video to VGA Adapter

Product ID: VID2VGATV3



This composite to VGA video converter provides a simple way to convert and scale composite and S-Video signals to VGA output, for use with computer monitors, projectors or HDTV sets.

Equipped with an on-screen display (OSD) menu and a toggle switch for simple configuration and selection of your video output settings, this compact S-Video to VGA video converter installs quickly and easily, for a true plug-and-play experience.

By using this AV to VGA adapter you'll be able to continue using your legacy equipment (VCR, DVD player, etc.) with your VGA display or monitor, ultimately saving the costs of upgrading your equipment. It's ideal for boardroom settings, medical imaging and watching old home videos on your VGA display or new HDTV.

The AV to VGA converter features an integrated video scaler circuit that dynamically converts the S-Video or composite video input signal, giving you multiple output resolutions to choose from, to ensure compatibility with your display or projector. It supports resolutions up to 1920x1200 @ 60Hz, so you can enjoy high-definition video without having to sacrifice picture quality.

VID2VGATV3 is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Display video from your legacy gaming console, DVD player or VCR onto a VGA monitor or HDTV
- Adapt VHS video in the classroom to newer televisions

- Convert legacy medical imaging equipment for display on computer monitors
- Display camcorder output on televisions or monitors equipped with VGA input
- Monitor security cameras with S-Video or composite signaling using VGA monitors or televisions
- Use in boardrooms for connecting legacy video equipment to new projectors

Features

- Convert and scale S-Video and composite input to VGA output
- Features on-screen display for simple output setting selection
- Supports high-definition resolutions up to 1920x1200 @ 60Hz
- Offers a pure hardware design, with no software installation required
- Video scaler accepts NTSC and PAL input

Hardware	Warranty	2 Years
	Active or Passive Adapter	Active
	AV Input	S-Video
	AV Input	Composite
	AV Output	VGA
	Audio	No
Performance	Supported Resolutions	1920x1200 (60Hz)
	Signal Levels	1920x1080
		1680x1050
		1600x1200
		1600x900
		1280x1024
		1024x768
		800x600
		Input
		Video @ 1V p-p, 75 ohm
	Y @ 1 V p-p, 75 ohm	
	Color @ 0.7V p-p, 75 ohm	
Connector(s)	Connector A	Composite Video (1 x RCA)
	Connector A	S-Video (4 pin, Mini-DIN)
	Connector B	VGA (15 pin, High Density D-Sub)
Power	Power Source	USB-Powered

Environmental	Operating Temperature	0C to 50C (32F to 122F)
	Storage Temperature	-10C to 80C (14F to 176F)
	Humidity	5~90% RH
Physical Characteristics	Color	Black
	Material	Plastic
	Product Length	2.6 in [66.000 mm]
	Product Width	2.3 in [58.000 mm]
	Product Height	0.8 in [20.000 mm]
	Weight of Product	1.7 oz [48.000 g]
Packaging Information	Package Length	5.9 in [1.5 cm]
	Package Width	4.4 in [1.1 cm]
	Package Height	1.1 in [28.000 mm]
	Shipping (Package) Weight	4.2 oz [120.000 g]
What's in the Box	Included in Package	Video Scaler Converter
	Included in Package	USB-A to USB Mini Cable
	Included in Package	Quick-Start Guide

****Product appearance and specifications are subject to change without notice.***

